

- QUICKLY SEALS, bonds, protects, insulates and waterproofs.
- CURES RAPIDLY at room temperature.
- EXCELLENT FOR USE in high moisture, indoor and outdoor applications.
- WITHSTANDS operating temperatures from -70°F to 400°F after curing.
- APPLY to surface within 0°F to 120°F temperature range.
- RESISTS sagging and slumping when applied overhead or on sidewall joints.
- ADHERES to metal, glass, silicone resin, most types of wood, vulcanized silicone, rubber, natural and synthetic fiber ceramic, and many plastic surfaces.
- MEETS NSF / ANSI #51 & FDA Federal Regulation No. 21, CFR 177.2600 standard
- MIL-A-46106A, and Federal Specifications TT-S-001543A and TT-S02300C when fully cured.

APPLICATIONS:

- "Form-In-Place" Gaskets • Electrical • Industrial
- Construction • Metalworking • And Many More

DIRECTIONS: *Please read entire label before use.*

1. Clean and dry all surfaces. Remove any oil and grease prior to application. Sealant adheres best to clean, unpainted surfaces.
2. Cut tip and attach nozzle. Cut nozzle at an angle to desired bead size.
3. Apply with a caulking gun, forcing sealant into the joint.
4. If further tooling is required, complete within 5 minutes. Remove excess sealant immediately with a dry paper towel.
5. Sealant "skins" in approximately 10 minutes, dries to the touch in one hour, and fully cures and bonds in 24 hours.
6. If gasket is not used in assembly, apply sealant to surface of one part and allow skin to form before assembling parts.
7. After sealant is completely cured, excess material can be removed by trimming with a sharp blade. Avoid undercutting the sealant.
8. If contents are not completely used, seal the nozzle with a suitable object (nail) for future use.
9. Not recommended for use involving continuous immersion in gasoline or head gasketing operations.

Precautionary Statements: Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Store away from incompatible materials. Do not store container above 100 °F/38 °C. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: Wash hands after handling.

Contains polydimethylsiloxane 70131-67-8, amorphous silica 7631-86-9, hydrotreated middle distillates 64742-46-7, aluminum 7429-90-5, titanium dioxide 13463-67-7, and carbon black 1333-86-4.

For additional information, consult SDS for this product.

VOC Category: Sealant or Caulking Compound	VOC Limit: 3%
Health: 1 Flammability: 1 Reactivity: 0 PPE: B	



RTV
Silicone
Adhesive & Sealant

Insulates • Bonds • Protects • Waterproofs

White

No. 14074
Item# 1004804

10.1 fl oz (298 mL)

KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

