



**Danger:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure.

**Precautionary Statements:** Obtain safety instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist/vapors. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

**First Aid:** If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.



# Minimal Expansion Foam

**Fills, Insulates & Seals  
All Direction Dispensing  
Reusable**



**DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED, EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN.**  
Read warnings on back panel.



No. 14077  
Item# 1004808

**Net Wt.  
12 oz (340 g)**

## CRC® Minimal Expansion Foam

Para obtener información adicional en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

**DIRECTIONS:** Read entire label before using this product. FOR INTERIOR USE ONLY.

1. Do not apply while equipment is energized. Product is extremely flammable when dispensing.
2. Wear gloves, eye protection and work clothes. Use drop cloths.
3. For best results, apply in temperatures between 60° and 100°F (16–38°C). Clean surfaces to be foamed with a CRC Cleaner.
4. Connect straw onto angle adapter, then carefully screw onto valve. Shake can vigorously for 30 seconds.
5. First practice dispensing foam onto scrap materials with the can in an upright position. The product is now ready to be applied while holding the can in any direction.
6. Fill gap no more than 1/3 full, allowing room for expansion.

Important: Foam will continue to dispense for a few seconds after releasing the trigger – keep the straw tip moving to reduce the possibility of overfilling. Foam is tack-free in 30 minutes and dries in 4 hours. Excess foam can be trimmed, sanded, caulked or plastered as necessary. Direct sunlight discolors foam if not painted or covered. Cured foam exposed to temperatures in excess of 116°C (240°F) may release hazardous decomposition products.

**CLEAN-UP:**

1. If wet foam contacts skin, clean immediately with a dry rag – do not use water.
2. Do not attempt to remove cured foam with solvents – cured foam wears off and is not harmful.

Contains chlorinated paraffins 63449-39-8, polymeric diphenylmethane diisocyanate 9016-87-9, 4,4-diphenylmethane diisocyanate 101-68-8, isobutane 75-28-5, tris(2-chloroisopropyl) phosphate 13674-84-5, dimethyl ether 115-10-6, propane 74-98-6, soybean oil 8001-22-7, and 2,2-dimorpholinyl diethyl ether 6425-39-4. For additional information, consult SDS for this product.

**Electrical Shock Hazard:** This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

R14175 1L15



**UNDERWRITERS LABORATORIES INC.**  
CLASSIFIED CAULKING AND SEALANT  
Surface Burning Characteristics Applied To  
Inorganic Reinforced Cement Board\*  
Flame Spread 10 Smoke Developed 15

\*Tested as applied in three 3/4" diameter beads 6" on center covering 12.5% of the exposed test sample area.