



Rust Converter

Instantly Stops Rust
Converts Rust to a Tough, Black Primer
Protects Surfaces for Years

*Para obtener información adicional en Español,
visite www.crcindustries.com.*

WARNING: MAY BE HARMFUL IF SWALLOWED.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.



No. 18419
Item# 1005248

Net Contents:
1 gal (3.78 L)

CRC Rust Converter

- NEUTRALIZES rust and converts it to a tough black primer in one easy step.
- No more scraping or sandblasting.
- STOPS old rust, and prevents new rust.
- Applications include: Vehicles, Trailers, Railings, Bridges, Equipment, Pipelines, Storage Tanks, Transmission Towers, etc.

DIRECTIONS: *Read entire label before using this product.*

1. Apply only when temperatures are between 50°F and 90°F.
2. Remove dirt, grease, oil and other contaminants.
3. Remove blistered or loose paint, and loose rust scale.
4. Use of rubber gloves and safety glasses is recommended.
5. Shake and stir well before using. Do not dilute product.
6. Pour estimated amount needed into a clean container. Material cannot be returned to original container after use.
7. For maximum penetration, work product into rusted surfaces with a synthetic bristle brush. For large areas, use a roller or sprayer.
8. Apply a second coat right after the first coat has dried. Apply in a cross direction of the first coat.
9. For best results, apply two thin coats. Wait 24 hours before painting.
10. Clean all painting equipment immediately after use with cold water.
11. Protect product from freezing in the container. Up to 500 sq. ft. coverage per gallon.

Warning

May cause damage to organs (kidney, liver, reproductive system).

Precautionary Statements

Do not breathe the mist or vapor. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Store locked up. Do not store container below 32 °F/0 °C. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid

If exposed or concerned: Call a poison center/doctor.

Contains water 7732-18-5, vinylidene dichloride acrylic copolymer latex, tannins 1401-55-4, and 2-butoxyethanol 111-76-2. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Health: 2 Flammability: 0 Reactivity: 1 PPE: B

VOC Content: 53.8 g/L

©2017 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Care)

www.crcindustries.com
Made in U.S.A. 17A

