

Easy and Effective

Protects against wear and corrosion. Lubricates moving parts for smooth, squeak-free operation. Adheres to metal surfaces for long-lasting performance. Quick, convenient spray gets to hard-to-reach places.

APPLICATIONS:

Hinges • Industrial Chains • Latches • Slides • Winches
Overhead Door Tracks • Thrust Bearings • Gears • Cables • Nuts/Bolts
Locks • Guide Rails • Springs • Bushings • Ball Joints
Pivot Points and all external moving parts

DIRECTIONS:

1. Disconnect power source to electrical equipment before spraying.
2. Shake well
3. Clean area to be lubricated
4. Spray in light, even coats
5. Use extension tube for hard-to-reach places

SPRAY GREASE



SPRAY GREASE

WHITE LITHIUM

LUBRICATES AND PROTECTS

No-Hassle Application

DANGER:
EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CAUSES SKIN IRRITATION. CONTENTS UNDER PRESSURE.
Read carefully precautions on back panel.

Contains hydrocarbon propellant 68476-86-8, isohexane 64742-49-0, 107-83-5, 110-54-3, petroleum distillates 64742-52-5, and titanium dioxide 13463-67-7.

DANGER: Contents extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Maintain ventilation during use and until vapors are gone. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid breathing vapor. Avoid contact with skin. Exposure can cause skin irritation, upper respiratory tract irritation, headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-222-1222. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, on the ground, or into any body of water. **ELECTRICAL SHOCK HAZARD:** This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire. **KEEP AWAY FROM CHILDREN**

For Safety Data Sheet visit www.amsoil.com.



WARNING: This product can expose you to titanium dioxide which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

AMSOIL INC., Superior, WI 54880 USA

Made in USA



PRODUCT CODE: GSP-SC

0417

NET WEIGHT 10 OZ (283 g)