

Read entire label before using this product.



# Driller Red Grease

## Hi-Temp • Extreme Pressure

## Premium Lithium Complex • NLGI Grade 2

- Premium quality lithium complex, Extreme Pressure (EP) grease
- “Tacky” stay-in-place formula
- Superior protection to lubricate a wide variety of severe duty drilling, industrial, mining and construction equipment
- Outstanding protection in wet environments
- 80+ Timken Load

Para obtener información adicional en Español, visite [www.crcindustries.com](http://www.crcindustries.com).



**WARNING:** Causes skin irritation. Causes serious eye irritation.

**Precautionary Statements:** Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves and eye/face protection. Wash thoroughly after handling. Store away from incompatible materials. Dispose of contents/container in accordance with local/regional/national regulations.

**First Aid:** If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Contains hydrotreated heavy naphthenic distillates 64742-52-5, lithium hydroxide solution 1310-66-3, solvent-refined residual oils 64742-01-4, and antimony dithiocarbamate 15890-25-2.

For additional information, consult SDS for this product.

**FOR EMERGENCIES CALL CHEMTREC: 1-800-424-9300**

Made in USA   
with Foreign and   
Domestic Components



Filling Date:

Batch Number:



©2019 CRC Industries, Inc.  
885 Louis Dr., Warminster, PA 18974  
800-521-3168 (Technical Info)  
800-272-4620 (Customer Care)  
[www.crcindustries.com](http://www.crcindustries.com) 19A

No. SL3650 / Item# 1007960

**35 lb (15.8 kg)**

