



A V I A T I O N

# Precision Contact Cleaner

NO RESIDUE/NO FLASH POINT



WARNING: VAPOR HARMFUL, EYE IRRITANT.  
CONTENTS UNDER PRESSURE.  
READ WARNINGS ON BACK PANEL.

Net Wt. 14 oz. (397 g) No. 10330



VOC Category: Electronic Cleaner VOC Limit: 75% by weight

HMS: Health: 2 Flammability: 1 Reactivity: 0 PPE: B

**ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from electrical shock.

1. May be harmful to some plastics. Test on a small area before using.
2. Spray until clean. Use extension tube for pinpoint cleaning.
3. Use an abrasive on surfaces with heavy carbon deposits or corrosion - remove residue with intermittent spray before reactivating system.
4. Periodic planned maintenance prolongs life expectancy of components and helps eliminate deposits that cause leakage. Use resistance measurements to determine frequency of application.
5. Do not use on energized equipment.

**DIRECTIONS:** Read entire label before using this product.

To View Emergency M.S.D.S.: Tear (DO NOT CUT) label by running fingernail between perforations. Fold back label. Do not remove until can is empty.

**WARNING:** Contains 1,1-Dichloro-1-fluoroethane 1717-00-6, and Carbon Dioxide 124-38-9. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in a well ventilated area. Avoid continuous breathing of vapors and spray mist. Avoid contact with skin and eyes. Overexposure to vapor may cause irritation to eyes and respiratory tract, dizziness and loss of consciousness. With high exposure levels, effects can include central nervous system depression and irregular heartbeats (cardiac arrhythmia). Deliberate misuse by concentrating and inhaling the contents may be harmful or fatal. Vapors reduce oxygen available for breathing and can cause asphyxiation. Vapors are heavier than air and can collect in low areas. pits, small rooms or other unventilated areas. If ventilation is not adequate, respiratory protection should be used. Death can occur without warning if too much is breathed. Vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. For skin contact, wash thoroughly. If swallowed, may be harmful or fatal. Do not induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately. For additional information, consult MSDS for this product. All used and unused product should be disposed of in conformance with local, state, and federal regulations.

**KEEP AWAY FROM CHILDREN**



06A CRC#495 Made in U.S.A.

- Fast-penetrating, high purity formula evaporates rapidly and leaves no residue to alter electrical properties
- Instantly removes grease, oil, dirt, flux and other contaminants
- Helps prevent contact failure or malfunction by dissolving and removing safety contaminants
- Material Safety Data Sheet printed on back of label for your convenience and safety (The CRC MSD[L]™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827)

WARNING: VAPOR HARMFUL, EYE IRRITANT.  
CONTENTS UNDER PRESSURE.

Precision Contact Cleaner  
Part # 10330 06A  
Net Wt. 14 oz. (397 g)  
www.crcindustries.com

©2006 CRC Industries, Inc., Warminster, PA 18974  
800-521-3168 (Technical Information)  
800-272-4260 (Customer Service)  
215-442-6260 (MSDS)  
CRC#495