

CRC Protector 100

WARNING: Contains Petroleum Distillate 8052-41-3, Hydrocarbon Resin, Alkyd Resin, NA Corrosion Inhibitor 57855-77-3 and Lanolin 8006-54-0. Progressively higher exposure to vapor may cause irritation to eyes and respiratory tract, headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. Product is combustible and should be kept from all flames and other ignition sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Vapors are heavier than air and can collect in low areas.

FIRST AID: In case of eye or skin contact flush with water for 15 minutes. If swallowed do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Vapors of this product may develop a flammable atmosphere. Keep away from flames, sparks, and ignition sources. Do not cut or weld containers due to explosion hazard. FOR SPILLS, use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal.

DISPOSAL: Unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. EMPTY containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimers. **DO NOT DUMP IN SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER.**

KEEP AWAY FROM CHILDREN

CRC

A V I A T I O N

Protector 100

**MEETS BMS 3-23
STOPS CORROSION
RESISTS HEAT, COLD, HUMIDITY,
SALT SPRAY, AND DIRT
LONG TERM PROTECTION
DEEP PENETRATING ABILITY**



CRC Protector 100

- Meets Boeing specification BMS 3-23
- Designed for use on all areas of the aircraft
- Excellent protection in all areas of the airframe where moisture and corrosive agents can concentrate
- Long term protection for all common aerospace alloys; reapplication recommended once a year.
- Deep penetrating ability allows Protector 100 to flow between metal parts to protect crevices and sandwiched areas
- A thin protective coating that resists heat, cold, humidity, salt spray and dirt
- A corrosion inhibitor that will displace water and leave a tack free film
- Can be diluted with petroleum solvents to control film thickness
- Petroleum solvents or Super Degreaser will remove cured film readily
- Can be applied with air or airless atomizing spray equipment

DIRECTIONS:

Read entire label before using this product.

Protector 100 can be applied by spray, brush, or in a dip tank. The dip tank should be covered to prevent evaporation.

For the thickest film and longest protection under adverse conditions, use Protector 100 undiluted. Two coats may be needed in areas subject to heavy corrosion.

For lighter duty protection, dilute Protector 100 with up to one part of light mineral spirits (1:1 dilution). Dilution may increase the drying time required to obtain a tack-free film.

Do not apply while equipment is energized.

For heavier film requirements use CRC Protector 1500.

Net Contents: 5 gal. (18.9 L) **Part No.** 10702

DANGER: COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED.
Read warnings on side panel.

