



A V I A T I O N

Protector™ 1500

MEETS BOEING BMS 3-29,
DOUGLAS DMS 2150 AND
DOUGLAS DMS 2414 TYPE 2
MAXIMUM PROTECTION
DEEP PENETRATING ABILITY
RESISTS TEMPERATURE CHANGES,
SALT SPRAY, AND CORROSION



DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 11 oz. (312 g) No. 10750

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE.

©1998 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Tech. Info.)
800-611-3801 (Aviation & Nat'l Acct.)
Net Wt. 11 oz. (312 g)
Part # 10750
Protector 1500
CRC#480D 98A



98A
CRC#480D
Made in U.S.A.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. DO NOT use with ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

1. Shake well before using.
2. Spray in even coats to protect metal surfaces.
3. Film thickness should be controlled at 0.75-1.0 mils dry film for optimum protection.
4. Allow film to dry thoroughly.
5. Invert can and spray several seconds to keep from clogging.
6. Do not apply while equipment is energized.

Directions: Read entire label before using this product.

- Meets Boeing BMS 3-29, Douglas DMS 2150 and Douglas DMS 2414 Type 2
- Maximum Corrosion Protection for all common aerospace alloys; reapplication recommended once every 3 years
- Deep penetrating ability allows Protector 1500 to flow between faying surfaces and give maximum protection
- Heavy Film Coating resists temperature changes, humidity, salt-spray, galley fluids and other contaminants
- Easy removability using CRC Super Degreaser
- Transparent Coating aids in visual surface detection without removal during inspections
- Fluorescent Dye allows for detectability when applied
- Minimal odor
- Material Safety Data Sheet printed on back of label for your convenience and safety (the CRC MSDS™ is a proprietary label removal system patented under US Patent No. 5,056,827)

To View Emergency M.S.D.S.: Tear (DO NOT CUT) label by running fingernail between perforations. Fold back label. Do not remove until can is empty.

KEEP AWAY FROM CHILDREN.

WARNING: Contains Petroleum Distillate 8052-41-3, Hydrocarbon Resin-N/A, Acetone 67-64-1, Corrosion Inhibitor 57855-77-3, Alkyd Resin-N/A, and Carbon Dioxide 124-38-9. Do not puncture, incinerate or store above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat sources. Product is flammable and should be kept from all flames and other ignition sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Use only in well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to vapor may cause irritation to the eyes and respiratory tract, headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. Deliberate misuse by concentrating and inaling the contents can be harmful or fatal. Vapors are heavier than air and can collect in low areas. FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, may be harmful or fatal. Do not induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately. For additional information consult the Material Safety Data Sheet for this product.