



- QUICKLY SEALS, bonds, protects, insulates and waterproofs.
- CURES RAPIDLY at room temperature.
- EXCELLENT FOR USE in high moisture, indoor and outdoor applications.
- WITHSTANDS operating temperatures from -70°F to 400°F after curing.
- APPLY to surface within 0°F to 120°F temperature range.
- RESISTS sagging and slumping when applied overhead or on sidewall joints.
- ADHERES to metal, glass, silicone resin, most types of wood, vulcanized silicone, rubber, natural and synthetic fiber ceramic, and many plastic surfaces.
- MEETS Federal Regulation No. 21 CFR 177.2600, MIL-A-46106, and Federal Specifications TT-S-001543A and TT-S02300 when fully cured.

**APPLICATIONS:**

- "Form-In-Place" Gaskets
- Electrical
- Industrial
- Construction
- Metalworking
- And Many More

**DIRECTIONS: Please read entire label before use.**

1. Clean and dry all surfaces. Remove any oil and grease prior to application. Sealant adheres best to clean, unpainted surfaces.
2. Cut tip and attach nozzle. Cut nozzle at an angle to desired bead size.
3. Apply with a caulking gun, forcing sealant into the joint.
4. If further tooling is required, complete within 5 minutes. Remove excess sealant immediately with a dry paper towel.
5. Sealant "skins" in approximately 10 minutes, dries to the touch in one hour, and fully cures and bonds in 24 hours.
6. If gasket is not used in assembly, apply sealant to surface of one part and allow skin to form before assembling parts.
7. After sealant is completely cured, excess material can be removed by trimming with a sharp blade. Avoid undercutting the sealant.
8. If contents are not completely used, seal the nozzle with a suitable object (nail) for future use.
9. Not recommended for use involving continuous immersion in gasoline or head gasketing operations.

**Warning**

Causes skin and eye irritation.

**Precautionary Statements**

Wear protective gloves. Wash hands thoroughly after handling. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. When exposed to water or humid air, product evolves acetic acid. When heated, product may form formaldehyde vapors. Store in a closed container. Store in a dry place. Dispose of contents/container in accordance with local/regional/national regulations. For additional information, consult SDS for this product.

**First Aid**

If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If inhaled: Call a physician immediately.

Contains Hydroxy-terminated polydimethylsiloxane (70131-67-8), Amorphous silica (7631-86-9), Ethyltriacetoxysilane (17689-77-9), Methyltriacetoxysilane (4253-34-3), Titanium dioxide (13463-67-7), Carbon black (1333-86-4) and other non-hazardous materials. This product contains a chemical known to the State of California to cause cancer.

**VOC Category:** Sealant or Caulking Compound **VOC Limit:** 3%

Health: 1\* Flammability: 1 Reactivity: 0 PPE: B



**RTV  
Silicone  
Adhesive & Sealant**

**Insulates • Bonds • Protects • Waterproofs**

**White**

**Part No. 14074**

**10.1 fl. oz. (299 mL)**

**WARNING:**

**UNCURED PRODUCT MAY IRRITATE EYES AND SKIN. KEEP AWAY FROM CHILDREN. Read warnings on back panel.**

