

- QUICKLY SEALS, bonds, protects, insulates and waterproofs.
- NON-CORROSIVE and low odor.
- CURES RAPIDLY at room temperature.
- HEAVY DUTY FORMULA is excellent for use in forming custom-shaped gaskets and seals with excellent adhesion and high chemical resistance.
- BONDS SOLIDLY without sag or shrink throughout a temperature range of -80°F to 500°F (up to 600°F intermittently).
- ADHERES to glass, metals, vinyl building products, concrete, most plastics and painted surfaces. Excellent for use in butt glazing and conventional glazing of most substrates. Also excellent for general purpose caulking.
- MEETS Federal Specification TT-S-001543 and TT-S-00230 when fully cured.

APPLICATIONS:

- "Form-In-Place" Gaskets
- Electrical
- Industrial
- Construction
- Metalworking
- And Many More

DIRECTIONS: Please read entire label before use.

1. Clean and dry all surfaces. Remove any oil and grease prior to application. Sealant adheres best to clean, unpainted surfaces.
2. Cut tip and attach nozzle. Cut nozzle at an angle to desired bead size.
3. Apply with a caulking gun, forcing sealant into the joint.
4. If further tooling is required, complete within 5 minutes. Remove excess sealant immediately with a dry paper towel.
5. Sealant "skins" in approximately 10 minutes, dries to the touch in one hour, and fully cures and bonds in 24 hours.
6. If gasket is not used in assembly, apply sealant to surface of one part and allow skin to form before assembling parts.
7. After sealant is completely cured, excess material can be removed by trimming with a sharp blade. Avoid undercutting the sealant.
8. If contents are not completely used, seal the nozzle with a suitable object (nail) for future use.
9. Not recommended for use involving continuous immersion in gasoline or head gasketing operations.

Warning

May cause an allergic skin reaction.



Precautionary Statements

Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing dust. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Store away from incompatible materials. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse

Contains Hydroxy-terminated polydimethylsiloxane (70131-67-8), Polydimethylsiloxane (63148-62-9), Iron oxide (1309-37-1), Methyl tri(ethylmethylketoxime) silane (22984-54-9) and Ethyl tri(ethylmethylketoxime) silane (2224-33-1). For additional information, consult SDS for this product.

VOC Category: Sealant or Caulking Compound **VOC Limit:** 3%

Health: 1 Flammability: 0 Reactivity: 1 PPE: B

High Temperature • Non-Corrosive • Low Odor

RTV Silicone Adhesive & Sealant

Red

Part No. 14075

10.1 fl. oz. (299 mL)

WARNING:

UNCURED PRODUCT MAY CAUSE AN ALLERGIC SKIN REACTION. KEEP AWAY FROM CHILDREN. Read warnings on back panel.

