



**Black RTV
Silicone Sealant**

- QUICKLY SEALS, bonds, protects, insulates and waterproofs.
- NON-CORROSIVE and low odor.
- CURES RAPIDLY at room temperature.
- HEAVY DUTY FORMULA is excellent for use in forming custom-shaped gaskets and seals with excellent adhesion and high chemical resistance.
- BONDS SOLIDLY without sag or shrink throughout a temperature range of -80°F to 450°F (up to 500°F intermittently).
- ADHERES to glass, metals, vinyl building products, concrete, most plastics and painted surfaces. Excellent for use in butt glazing and conventional glazing of most substrates. Also excellent for general purpose caulking.
- MEETS Federal Specification TT-S-001543 and TT-S-00230 when fully cured.

APPLICATIONS:

- "Form-In-Place" Gaskets
- Electrical
- Industrial
- Construction
- Metalworking
- And Many More

DIRECTIONS: Please read entire label before use.

1. Clean and dry all surfaces. Remove any oil and grease prior to application. Sealant adheres best to clean, unpainted surfaces.
2. Cut tip and attach nozzle. Cut nozzle at an angle to desired bead size. Puncture inner seal at base of nozzle.
3. Apply with a caulking gun, forcing sealant into the joint.
4. If further tooling is required, complete within 5 minutes. Remove excess sealant immediately with a dry paper towel.
5. Sealant "skins" in approximately 10 minutes, dries to the touch in one hour, and fully cures and bonds in 24 hours.
6. If gasket is not used in assembly, apply sealant to surface of one part and allow skin to form before assembling parts.
7. After sealant is completely cured, excess material can be removed by trimming with a sharp blade. Avoid undercutting the sealant.
8. If contents are not completely used, seal the nozzle with a suitable object (nail) for future use.
9. Not recommended for use involving continuous immersion in gasoline or head gasketing operations.

WARNING: Contains Calcium Carbonate 1317-65-3, Amorphous Silica 7631-86-9, Methyl Tris (Methyl Ethyl Ketoxime Silane) 22984-54-9 and Vinyl Tris (Methyl Ethyl Ketoxime Silane) 2224-33-1. Product may release a small amount of Methyl Ethyl Ketoxime 96-29-7 when curing. Uncured sealant may cause skin, eye and respiratory system irritation. Use only in a well ventilated area. **FIRST AID:** In case of eye contact, flush eyes immediately with running water for 20 minutes and obtain medical attention immediately. In case of skin contact, remove from skin and flush with water. In case of inhalation discomfort, remove to fresh air. For severe overexposure, call a physician immediately.

KEEP AWAY FROM CHILDREN

All used and unused product should be disposed of in conformance with local, state and federal regulations.

©1999 CRC Industries, Inc. Made in U.S.A. 99A
 Warminster, PA 18974
 800-521-3168 (Technical Information)
 800-272-4620 (Customer Service)
 215-442-6260 (MSDS)
 www.crcindustries.com



High Pressure ∇ Non-Corrosive ∇ Low Odor

Black

Part No. 14076
 Net 10.3 fl. oz.

WARNING:
 UNCURED PRODUCT
 MAY IRRITATE EYES.
 Read warnings on back panel.