



- QUICKLY SEALS, bonds, protects, insulates and waterproofs.
- CURES RAPIDLY at room temperature.
- GRAY FORMULA is superb in cosmetic and window applications.
- BONDS SOLIDLY throughout a temperature range of -70°F to 400°F.
- RESISTS sagging and slumping when applied overhead or on sidewall joints.
- ADHERES to metal, glass, silicone resin, most types of wood, vulcanized silicone, rubber, natural and synthetic fiber ceramic, painted and many plastic surfaces.
- MEETS Federal Regulation No. 21 CFR 175.105, MIL-A-46106, Type 1 and Federal Specifications TT-S-001543A Class B and TT-S-00230C Type 2, Class B when fully cured.

DIRECTIONS: Please read entire label before use.

1. Clean and dry all surfaces. Remove any oil and grease prior to application. Sealant adheres best to clean, unpainted surfaces.
2. Cut tip and attach nozzle. Cut nozzle at an angle to desired bead size.
3. Apply with a caulking gun, forcing sealant into the joint.
4. If further tooling is required, complete within 5 minutes. Remove excess sealant immediately with a dry paper towel.
5. Sealant "skins" in approximately 10 minutes, dries to the touch in one hour, and fully cures and bonds in 24 hours.
6. If gasket is not used in assembly, apply sealant to surface of one part and allow skin to form before assembling parts.
7. After sealant is completely cured, excess material can be removed by trimming with a sharp blade. Avoid undercutting the sealant.
8. If contents are not completely used, seal the nozzle with a suitable object (nail) for future use.
9. Not recommended for use involving continuous immersion in gasoline or head gasketing operations.

Warning

Causes skin and eye irritation.
Suspected of causing cancer.

Precautionary Statements

Obtain special instructions before

use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Store in a closed container. Store in a dry place. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. When exposed to water or humid air, product evolves acetic acid. When heated, product may form formaldehyde vapors. For additional information, consult SDS for this product.

First Aid: If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention. If inhaled: Call a physician immediately.

Contains Polydimethylsiloxane, hydroxyl-terminated (70131-67-8), Ethyltriacetoxysilane (17689-77-9), Methyltriacetoxysilane (4253-34-3), Titanium dioxide (13463-67-7), Carbon black (1333-86-4) and other non-hazardous materials. This product contains a chemical known to the State of California to cause cancer.

VOC Category: Sealant or Caulking Compound **VOC Limit:** 3%

Insulates • Bonds • Protects • Waterproofs

RTV Silicone Adhesive & Sealant

Gray

Part No. 14079

Net 10.1 fl. oz.

WARNING:

UNCURED PRODUCT MAY IRRITATE EYES AND SKIN. KEEP AWAY FROM CHILDREN. Read warnings on back panel.

