

CRC® Food Zone Silicone Sealant – White

- QUICKLY SEALS, bonds, protects, insulates and waterproofs.
- CURES RAPIDLY at room temperature.
- BONDS SOLIDLY throughout a temperature range of -70°F to 400°F.
- RESISTS sagging and slumping when applied overhead or on sidewall joints.
- ADHERES to metal, glass, silicone resin, most types of wood, vulcanized silicone, rubber, natural and synthetic fiber ceramic, painted and many plastic surfaces.

DIRECTIONS: Please read entire label before use.

1. Clean and dry all surfaces. Remove any oil and grease prior to application. Sealant adheres best to clean, unpainted surfaces.
2. Cut tip and attach nozzle. Cut nozzle at an angle to desired bead size.
3. Apply with a caulking gun, forcing sealant into the joint.
4. If further tooling is required, complete within 5 minutes. Remove excess sealant immediately with a dry paper towel.
5. Sealant "skins" in approximately 10 minutes, dries to the touch in one hour, and fully cures and bonds in 24 hours.
6. If gasket is not used in assembly, apply sealant to surface of one part and allow skin to form before assembling parts.
7. After sealant is completely cured, excess material can be removed by trimming with a sharp blade. Avoid undercutting the sealant.
8. If contents are not completely used, seal the nozzle with a suitable object (nail) for future use.
9. Not recommended for use involving continuous immersion in gasoline or head gasketing operations.

Warning

Causes skin and eye irritation.

Precautionary Statements

Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. When exposed to water or humid air, product evolves acetic acid. When heated, product may form formaldehyde vapors. Wash hands thoroughly after handling. Wear protective gloves. Keep container tightly closed. Store in a dry place. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Contains Hydroxy-terminated polydimethylsiloxane (70131-67-8), Amorphous silica (7631-86-9), Hydrotreated middles distillates (64742-46-7), Polydimethylsiloxane (63148-62-9), Ethyltriacetoxysilane (17689-77-9), Methyltriacetoxysilane (4253-34-3), Aluminum (7429-90-5), Titanium dioxide (13463-67-7) and Carbon black (1333-86-4). This product contains a chemical known to the State of California to cause cancer. For additional information, consult SDS for this product.

VOC Category: Sealant or Caulking Compound **VOC Limit:** 3%



Food Zone Silicone Sealant

WHITE

**Certified for use
in Food Plants**

**Meets NSF / ANSI #51 &
FDA Reg 21, CFR 177.2600**



Part No. 14082

10.1 fl. oz. (299 mL)

WARNING:

**UNCURED PRODUCT MAY
IRRITATE EYES AND SKIN.
KEEP AWAY FROM CHILDREN.**
Read warnings on back panel.

