



CRC

Perma-Mend™ Repair Patch

**UV Light Activated, Fiberglass
Reinforced, Self-Adhesive Repair Patch**

No Mixing, No Measuring, No Mess, Thousands of Applications



No. 14096

WARNING: CAUSES EYE IRRITATION.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

**9 in. x 12 in.
(22.9 cm x 30.5 cm)**

Properties: Perma-Mend™ is a very unique, easy-to-use UV or sunlight activated, self adhesive repair patch. It is fiberglass reinforced Polyester with extremely good adhesion properties for long lasting repairs. Perma-Mend™ is non-flammable, non-toxic, and adhesive is not harmful to skin. Easy to apply, no mixing, no weighing – one step, no mess.

- Easy application – just cut, peel and stick – finished
- Extremely durable, Fiberglass, reinforced Polyester/Plastic
- Flexible and waterproof
- Weather and UV resistant
- Can be drilled, tapped, sanded and painted in less than an hour
- Resistant against many chemicals, solvents and oils
- Constantly temperature resistant from -40°C to 200°C
- No shrinkage or expansion during the application or after curing
- Bonds to all surfaces except Polypropylene (PP)
- Fast curing (starting within 5 minutes depending on UV intensity)
- Rated up to 2200 PSI when properly applied

Applications:

Industry: Repair and maintenance of roofs, steps, tanks, pipes, lines, gutters, switch boxes, etc.

Automotive/truck/transport: Bumpers, radiators, rusted areas and exhaust leaks, fuel tanks and lines, box bodies, head lamp housings, all lands of plastics and body components.

Hobby,Sport DIY: Jet skis, canoes, boats, surf boards, prototyping, modeling, windows, doors, fences, roofs, drainage lines, pools, spas, garden equipment, sanitation systems, ball tanks and lines, sporting equipment and various other surfaces like wood, metal, glass, ceramics, concrete and plastics

DIRECTIONS: Read entire label before using this product.

1. Surface should be cleaned, dry and free of any contaminates.
2. Remove black protective sheet. Cut Perma-Mend™ into any size you want without exposing to UV/Sunlight.
3. Remove white backing tape to expose the sticky resin. Apply patch then remove transparent film backing on other side after application
5. Apply Perma-Mend™ to repair area with sticky side down. Press firmly and expose to UV/Sunlight. Curing times depend on UV intensity, between 5 minutes (sunny) and 50 minutes (cloudy).

Contains Mineral fillers, Fiberglass, Polyester resin and Styrene (100-42-5). For additional information, consult SDS for this product. If in eyes: Rinse cautiously with water for several minutes. If eye irritation persists: Get medical attention.

©2015 CRC Industries, Inc., Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Care)
215-442-6260 (SDS)

15A www.crcindustries.com

