



- Paintable
- High Performance, Excellent Adhesion
- Resistant to UV degradation and Weathering
- Mold and Mildew Resistant
- Resists Stains and Dirt
- Bonds to a Variety of Common Substrates
- Extremely Flexible and Durable (Will not crack or dry out)
- Meets ASTM C-834-76

DIRECTIONS: *Please read entire label before use.*

1. Surface Preparation: Surface should be clean and dry. Do not use solvents to clean joints unless surface can dry thoroughly before application of sealant. Remove loose dust or dirt. Contamination from curing agents and form releases should be avoided. Unprimed adhesion can be easily tested by applying a small trial bead and allowing 7 days for maximum adhesion to occur.
2. Cut tip and apply nozzle. Apply with conventional caulking equipment.
3. For tooling ease, tool within 10 minutes of the application.

Warning

Causes eye irritation.

Precautionary Statements

Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash hands thoroughly after handling. Keep container tightly closed. Store in a dry place. Dispose of contents/ container in accordance with local/regional/national regulations. For additional information, consult SDS for this product.

First Aid

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Contains Acrylic emulsion (Proprietary), Calcium carbonate (1317-65-3), Benzoate ester mixture (Proprietary), Titanium dioxide (13463-67-7) and Ammonia (7664-41-7).

This product contains a chemical known to the State of California to cause cancer.

VOC Category: Non-chemically Curing Sealant or Caulking Compound	VOC Limit: 1.5%
--	------------------------

Health: 1 Flammability: 1 Reactivity: 0 PPE: B



Insulates • Bonds • Protects • Waterproofs

Siliconized

Acrylic Latex

Caulk

White

Part No. 14108

10.2 fl. oz. (302 mL)

WARNING:
CAUSES EYE IRRITATION.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.