



CABLE
GLIDETM

Made in USA

Pre-Lube PacTM

"ALL-SEASON"

Cable Pulling Lubricant
with **TEFLON**[®]



Part No. 14155 • Net Contents: 2 quarts (1.89L)

READ ALL WARNINGS

Wide temperature range
Non-staining
Water clean-up

Safe for all cable types: Power, Data Com, Fiber

With CRC Cable Glide[™], cable virtually "glides through conduit, saving time, money, and effort." CRC Cable Glide[™] - "All Season" Cable Pulling Lubricant - combines the lubricating power of Teflon[®] with a water-based gel to create a cable lubricant that goes on smooth, clings firmly and significantly reduces friction. The unique viscosity of the "All Season" gel allows Cable Glide[™] to be applied by hand, cloth, or as a Pre-Lube Pac[™] without falling off cables before they enter the conduit. Even more inviting, the low cost of CRC's "All Season" formula permits year-round use of Cable Glide[™], eliminating the need to order more than one lubricant.

CRC Cable Glide[™] is water soluble - it cleans-up easily with soap and water and will not stain fabrics, clothing or skin like wax-based and dyed products.

Advantages:

- Developed for use on High Voltage, Data Com and Fiber Optic Cables.
- Safe for use on all cable jackets, insulating materials, wire coating and conduit types.
- Achieves superior lubricating properties without the use of wax or Paraffin's, allowing easy addition, removal and repull of cables.
- Exceptional freezer/thaw stability - maintains lubricating efficiency in extreme weather conditions.
- Temperature range: 15°F to 110°F.
- If freezing occurs, product can be thawed and used immediately without mixing.
- May be used below 15°F if conditions permit.
- Non-flammable, non-toxic and non-conductive. Allow for venting prior to energizing.

Warning: Contains: Water 7732-18-5, Methanol 67-56-1, Isopropanol 67-63-0, Propylene Glycol 57-55-6. This product is conductive when applied. Do not take internally. If product comes in contact with eyes or mouth, flush with water. Wash hands thoroughly after handling. Keep container closed.

First Aid: In case of eye contact, flush with water for 15 minutes. If swallowed, drink large amounts of water. For severe overexposure, call a physician. For spills: use proper protective equipment. Take precaution as necessary to prevent contamination of ground or surface water.



97A
CRC#561B

Disposal: Unused contents and containers must be disposed of in accordance with all federal, state and local regulations. EMPTY containers may be offered to a qualified reclaimers. Unused contents may be offered to a licensed reclaimers. DO NOT DUMP INTO SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. For additional information consult the Material Safety Data Sheet for this product.

Directions for Pre-Lube Pac[™] use: Read entire label before using this product.
Method A:

1. When possible, pour Cable Glide[™] into conduit pipe to start initial lubrication.
2. Attach **Pre-Lube Pac[™]** to wire/cable pulling device well ahead of cable. Using a cable tie or similar device, fasten the **Pre-Lube Pac[™]** just behind the metal closure ring to the winch rope.
3. Slice bag down its pre-marked length as it enters the conduit.
4. Remove bags at far end of run.

Method B:

1. Slit bags as in Method A.
2. Place in conduit.
3. Repeat as required.
4. Start pull, remove bags from far end of run. Always remove Cable Glide[™] from electrical conduit, fuses, buss bars and connectors.

Quantities Needed:

- May vary by a multiple of 2 depending on length of conduit, O.D. of wire, existing condition of conduit, bends and pulling equipment in use. One **Pre-Lube Pac[™]** is recommended per 100 ft. of 3 in. conduit.

Storage: Avoid freezing and prolonged exposure to direct sunlight. Store unused

Pre-Lube Pac[™] in their closed cardboard shipping container.
If removed from container. Store bags flat, do not bend.

CRC Industries, Inc.
Warminster, PA 18974
©1997 CRC Industries, Inc.
Made in USA

Customer Service (800) 272-4620
Technical Service (800) 521-3168

