

FLEETWERKS™ HEAVY DUTY

CRC FLEETWERKS Heavy Duty Gel Engine Degreaser is specifically formulated for heavy duty equipment, trucks, fleets and more. Penetrates and removes the most stubborn baked on engine greases and road grimes. Unique gel formula clings to all surfaces longer and penetrates deeper than conventional engine degreasers. When rinsed with water the gel formula emulsifies and washes greases away.

DIRECTIONS: Read entire label before use.

1. Engine must be off and cool. 2. Remove air cleaner cover and filter. Cover air intake system (or carburetor), distributor, and all exposed wiring and electronic components. Limit rinse water contact on all underhood wiring and electronic sensors to prevent performance problems. 3. Spray on dry engine. 4. Allow to penetrate and clean for 10 to 15 minutes. Brush heavy deposit areas if required. 5. Before rinsing, place a rinse collection receptacle underneath the engine. Disposal on ground is prohibited in California. 6. Rinse from the top down using a fine stream of water. Use a minimum amount of water. Do not dispose of rinse water on the ground, in sewers, floor drains or other waterways. 7. Rinse water must be disposed of in conformance with local, state and federal regulations. 8. Remove all covers from carburetors, distributors, air intake system and electronic components. Replace all removed parts. Immediately start engine and let idle for 10-15 minutes to dry.

IMPORTANT: Wipe product immediately from exterior painted surface to avoid streaking and dewaxing. Avoid use on asphalt black top or other surfaces affected by organic solvents.

Contains petroleum distillates 64742-47-8, 68476-80-9, acetone 67-64-1, ethoxylated nonylphenol 68412-54-4, carbon dioxide 124-38-9, 2-butoxyethanol 111-76-2, xylene 1330-20-7, and ethylbenzene 100-41-4.

DANGER: Contents are flammable. Vapors can accumulate and create a flammable atmosphere. Do not use near open flame or other sources of ignition. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120 °F/ 49 °C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Exposure to liquid or vapors can cause serious eye damage, skin irritation, upper respiratory tract irritation, and headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation, use respiratory protection, or leave the area.

FIRST AID: In case of eye or skin contact, rinse immediately with plenty of water for at least 15 minutes. Get medical attention immediately. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-222-1222.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state, and federal regulations. DO NOT dump in sewers, floor drains, on the ground or into any body of water.

ELECTRICAL SHOCK HAZARD: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

KEEP AWAY FROM CHILDREN

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

©2019 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical Info) www.crcindustries.com
800-272-8963 (Customer Care) 19A

Made in USA 
with Foreign and
Domestic Components



FLEETWERKS™
HEAVY DUTY



ENGINE DEGREASER

GEL FORMULA

**SPECIALLY FORMULATED
FOR HEAVY EQUIPMENT**



DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CAUSES EYE BURNS. SKIN IRRITANT. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 15 oz (425 g)

Item# 1751348

Formula item# 1002588

Rev 19A

Label item# 1751349