

©1997 CRC Industries, Inc. Warminster, PA 18974 800-521-3168 (Tech. Info.) 800-272-4620 (Cust. Serv.)
All Purpose Enamel Spray Paint Net Wt. 10 oz. (284g)

DANGER! EXTREMELY FLAMMABLE. VAPOR HARMFUL.
 CONTENTS UNDER PRESSURE.



All-Purpose Enamel Spray Paint

- Fast Drying
- Indoor/Outdoor Use

TECHNICAL DATA

Surfaces: Metal, wood, paper and cloth
Resistance: Heat — 180°F (82°C)
Resin System: Vinyl, toluene oil enamel
Abrasion: — good
Dry Time: Tack free — 15 to 30 minutes
Corrosion: — good
Fully dry: — 1 hour
Solvents: — fair
Recoat: — Within 2 hours or after 24 hours
VOC COMPLIANT

Parrot Green 18003



Net Wt. 10 oz. (284g)

DANGER! EXTREMELY FLAMMABLE.
 VAPOR HARMFUL. CONTENTS UNDER PRESSURE.
 READ WARNINGS ON BACK PANEL.



97A
 Made in U.S.A.



SPECIAL USAGE WARNINGS:
 • Contents extremely flammable.
 • Do not smoke while spraying.
 • Extinguish all flames, pilot lights and heaters.
 • Do not apply white equipment is energized.
 • Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone.
ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

DIRECTIONS: Read entire label before using this product.
 1. Shake vigorously for at least one minute after ridding of mixing ball its head. Shake intermittently during application.
 2. For best results, spray at room temperature (70°F).
 3. Surface to be painted should be clean and dry. Remove dirt, grease, oil, rust, scale and other contaminants.
 4. Mask areas not to be sprayed to protect from overspray.
 5. Hold can 12 to 16 inches from surface. Press spray button firmly. Do not apply with continuous spray. Use back and forth motion.
 6. For best results 3-4 thin coats are recommended rather than one heavy coat. Recoat within 2 hours or after 24 hours.
 7. To prevent valve from clogging after spraying, turn can upside down and press sprayhead for about 3 seconds. This will clean paint from siphon tube and valve. If spray button is clogged, remove from can and run knife edge through tiny slit at end of spray button stem. Clear spray button orifice by inserting pin. Do not insert pins or other sharp objects into valve opening of can.
 8. Coverage: 15 to 20 sq. ft.

To view Emergency M.S.D.S.: Tear (DO NOT CUT) label by running fingernail between perforations. Fold back label. Do not remove until can is empty.

WARNING: Contains Acetone 67-64-1, Aliphatic Hydrocarbon 64742-89-8, Xylene 1330-20-7, Aromatic Hydrocarbon 64742-95-6 & Propene/Isobutane Mixture 68476-86-8. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Harmful or fatal if swallowed. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Avoid contact with skin or eyes. Overexposure to vapor may cause irritation to eyes, respiratory irritation, headaches, dizziness and nausea. Use with adequate ventilation. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. For skin contact, wash area thoroughly with water. If swallowed, do not induce vomiting. Call a physician. If too much is breathed, remove to fresh air. For severe overexposure call a physician immediately.

KEEP AWAY FROM CHILDREN