

WARNING: Contains Acetone 67-64-1, Xylene 1330-20-7 & Propane/isobutane Mixture 68476-86-8. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Harmful or fatal if swallowed. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Avoid contact with skin or eyes. Overexposure to vapor may cause irritation to eyes; respiratory irritation, headaches, dizziness and nausea. Use with adequate ventilation. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. For skin contact, wash area thoroughly with water. If swallowed, do not induce vomiting. Call a physician. If too much is breathed, remove to fresh air. For severe overexposure call a physician immediately.

To view Emergency M.S.D.S.: Tear (DO NOT CUT) label by running fingernail between perforations. Fold back label. Do not remove until can is empty.

- For general use in everyday factory and contractor applications
- Resists corrosion, abrasion, fading, and heat
- Use on wood, metal, masonry, and glass
- Use with CRC's All Purpose Enamel Spray Primer for best results

M.S.D.S. [L]™ "Material Safety Data Label" is a current Material Safety Data Sheet printed on the reverse side of the label. (The CRC M.S.D.S. [L]™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827)



97A
Made in U.S.A.

Aluminum 18007



Net Wt. 10 oz. (284g)

DANGER! EXTREMELY FLAMMABLE.
VAPOR HARMFUL. CONTENTS UNDER PRESSURE.
READ WARNINGS ON BACK PANEL.



All-Purpose Enamel Spray Paint

- Fast Drying Use
- Indoor/Outdoor Use

TECHNICAL DATA

Surfaces: Metal, wood, paper and cloth
 Resistance: Heat — 180°F. (82°C)
 Resin System: Vinyl toluene oil enamel
 Abrasion — good
 Dry Time: Tack free — 15 to 30 minutes
 Corrosion — good
 Fully dry — 1 hour
 Solvents — fair
 VOC COMPLIANT
 Recoat — Within 2 hours or after 24 hours

- DIRECTIONS:** Read entire label before using this product.
1. Shake vigorously for at least one minute after rattling or mixing ball is heard. Shake intermittently during application.
 2. For best results, spray at room temperature (70°F).
 3. Surface to be painted should be clean and dry. Remove dirt, grease, oil, rust, scale and other contaminants.
 4. Mask areas not to be sprayed to protect from overspray.
 5. Hold can 12 to 16 inches from surface. Press spray button firmly.
 6. For best results 3-4 thin coats are recommended rather than one heavy coat. Recoat within 2 hours or after 24 hours.
 7. To prevent valve from clogging after spraying, turn can upside down and press sprayhead for about 3 seconds. This will clean paint from siphon tube and valve. If spray button is clogged, remove from can and run knife edge through tiny slit at end of spray button stem. Clear spray button orifice by inserting pin. Do not insert pins or other sharp objects into valve opening of can.
 8. Coverage: 15 to 20 sq. ft.

ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

SPECIAL USAGE WARNINGS:

- Contents extremely flammable.
- Do not smoke while spraying.
- Extinguish all flames, pilot lights and heaters.
- Vapors will accumulate readily and may ignite. Use only with adequate ventilation.
- Vapors will accumulate readily and may maintain ventilation during use and until all vapors are gone.

DANGER! EXTREMELY FLAMMABLE. VAPOR HARMFUL.
CONTENTS UNDER PRESSURE.

All Purpose Enamel Spray Paint
 Part # 18007
 Net Wt. 10 oz. (284g)
 ©1997 CRC Industries, Inc.
 Warminster, PA 18974
 800-521-3168 (Tech. Info.)
 800-272-4620 (Cust. Serv.)