

WARNING: Contains Acetone 67-64-1, Toluene 108-88-3, Xylene 1330-20-7, Ethylbenzene 100-41-4, Methyl Isobutyl Ketone 108-10-1, Propane 74-98-6 and isobutane 75-28-5. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is extremely flammable and should be kept from all flames and other ignition sources. Harmful or fatal if swallowed. This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Avoid contact with skin or eyes. Overexposure to vapor may cause irritation to eyes, respiratory irritation, headaches, dizziness and nausea. Use with adequate ventilation. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. For skin contact, wash area thoroughly with water. If swallowed, do not induce vomiting. Call a physician. If too much is breathed, remove to fresh air. For severe overexposure call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product. **KEEP AWAY FROM CHILDREN**

To view Emergency M.S.D.S.: Tear (DO NOT CUT) label by running fingernail between perforations. Fold back label. Do not remove until can is empty.

- For general use in everyday factory and contractor applications.
- Resists corrosion, abrasion, fading, and heat.
- Use on wood, metal, masonry, and glass.
- Use with CRC's All Purpose Enamel Spray Primer for best results
- M.S.D.L.™ ("Material Safety Data Label") is a current Material Safety Data Sheet printed on the reverse side of the label. (The CRC M.S.D.L.™ is a proprietary label U.S. Patent No. 5,056,827)

SPECIAL USAGE WARNINGS:

- Do not smoke while spraying.
- Contents extremely flammable.
- Extinguish all flames, pilot lights and heaters.
- Vapors will accumulate readily and may ignite. Use only with adequate ventilation.
- Vapors will accumulate readily and may maintain ventilation during use and until all vapors are gone.

ELECTRICAL SHOCK HAZARD: This can will

conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

1. Shake vigorously for at least one minute after rattling of mixing ball is heard. Shake intermittently during application.
2. For best results, spray at room temperature (70°F).
3. Do not use sharp object to remove overcap.
4. Surface to be painted should be clean and dry. Remove dirt, grease, oil, rust, scale and other contaminants.
5. Mask areas not to be sprayed to protect from overspray. Do not apply to be painted from surface. Press spray button firmly.
6. Hold can 6 to 10 inches from surface. Use back and forth motion, keeping can in a level line with surface.
7. For best results 3-4 thin coats are recommended rather than one heavy coat. Recoat within one hour or after seventy-two hours.
8. To prevent valve from clogging after spraying, turn can upside down and press sprayhead for about 3 seconds. This will clean paint from siphon tube and valve. If spray button is clogged, remove from can and run knife edge through tiny slit at end of spray button stem. Clear spray button orifice by inserting pin. Do not insert pins or other sharp objects into valve opening of can.
9. Coverage - 15 to 20 sq. ft.

CRC®

All-Purpose Enamel Spray Paint

- Fast Drying Use
- Indoor/Outdoor Use

TECHNICAL DATA

Surfaces: Metal, Wood, Paper & Cloth
 Resin System: Alkyd Enamel
 Dry Time: Recoat --- 300 F. (149 C)
 Abrasion --- good
 Adhesion --- good
 Toughness --- good
 Track free --- 15 to 30 minutes
 Fully dry --- 1 hour
 Recoat --- Within 1 Hour or after 72 Hours
VOC COMPLIANT

Flat White 18009



Net Wt. 10 oz. (284g)

DANGER! EXTREMELY FLAMMABLE.
 HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL.
 EYE & SKIN IRRITANT. CONTENTS UNDER PRESSURE.
 READ WARNINGS ON BACK PANEL.



01A
 Made in Canada



DANGER! EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. EYE & SKIN IRRITANT. CONTENTS UNDER PRESSURE.

All Purpose Enamel
 Spray Paint
 Part # 18009
 Net Wt. 10 oz. (284g)
 www.crcindustries.com
 ©2001 CRC Industries, Inc.
 Warrington, PA 18974
 800-521-3168 (Tech. Info.)
 800-272-4620 (Cust. Serv.)
 215-442-6260 (MSDS)