

WARNING: Contains Acetone 67-64-1, Toluene 108-88-3, Xylene 1330-20-7, Ethylbenzene 100-41-4, Methyl Isobutyl Ketone 108-10-1, Dimethyl Ether 115-10-6, Propane 44-79-6 and Isobutane 75-28-5. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is extremely flammable and should be kept from all flames and other ignition sources. Harmful or fatal if swallowed. Inhalation causes irritation to eyes, respiratory irritation, headaches, dizziness and nausea. Use with adequate ventilation. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. For skin contact, wash area thoroughly with water. If swallowed, do not induce vomiting. Call a physician. If too much is breathed, remove to fresh air. For severe overexposure call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product. **KEEP AWAY FROM CHILDREN**

To view Emergency M.S.D.S.: Tear (DO NOT CUT) label by running fingernail between perforations. Fold back label. Do not remove until can is empty.

- DIRECTIONS:** Read entire label before using this product.
1. Shake vigorously for at least one minute after rattling or mixing ball is heard. Shake intermittently during application.
 2. For best results, spray at room temperature (70°F).
 3. Do not use sharp object to remove overlap.
 4. Surface to be painted should be clean and dry. Remove dirt, grease, oil, rust, scale and other contaminants.
 5. Mask areas not to be sprayed to protect from overspray.
 6. Hold can 6 to 10 inches from surface. Press spray button firmly.
 7. Do not apply with continuous spray. Use back and forth motion, keeping can in a level line with surface.
 8. For best results 3-4 thin coats are recommended rather than one heavy coat. Recoat within one hour.
 9. To prevent valve from clogging after spraying, turn can upside down and press sprayhead for about 3 seconds. This will clean paint from can and run knife edge through tiny slit at end of spray button stem. Clear spray button orifice by inserting pin. Do not insert pins or other sharp objects into valve opening of can.
9. Coverage: 15 to 20 sq. ft.



All-Purpose Enamel Spray Paint

- Fast Drying
- Indoor/Outdoor Use

TECHNICAL DATA

Surfaces: Metal, Wood, Paper & Cloth
 Resistance: Heat — 300°F (149°C)
 Resin System: Alkyd Enamel
 Abrasion — good
 Dry Time: Tack free — 15 to 30 minutes
 Corrosion — good
 Solvents — fair
 VOC COMPLIANT
 Recoat — Within 1 Hour



SPECIAL USAGE WARNINGS:
 • Contents extremely flammable.
 • Do not smoke while spraying.
 • Extinguish all flames, pilot lights and heaters.
 • Do not apply while equipment is energized.
 • Vapor will accumulate readily and may ignite. Use only with adequate ventilation.
 • Maintain ventilation during use and until all vapors are gone.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

- For general use in everyday factory and commercial applications.
- Resists corrosion, abrasion, fading, and heat.
- Use on wood, metal, masonry, and glass.
- Use with CRC's All Purpose Enamel Spray Primer for best results.
- M.S.D. ("Material Safety Data Label") is a current Material Safety Data Sheet printed on the reverse side of the label. (The CRC system patented under U.S. Patent No. 5,056,827)



02A
 Made in Canada

Machinery Dark Gray 18011



Net Wt. 10 oz. (284g)

DANGER! EXTREMELY FLAMMABLE.
 HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL TO EYE & SKIN IRRITANT. CONTENTS UNDER PRESSURE.
 READ WARNINGS ON BACK PANEL.

©2002 CRC Industries, Inc.
 Warminster, PA 18974
 800-521-3168 (Tech. Serv.)
 215-442-6280 (MSDS)
 All Purpose Enamel
 Spray Paint
 Part # 18011
 Net Wt. 10 oz. (284g)
 www.crcindustries.com

DANGER! EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL, EYE & SKIN IRRITANT. CONTENTS UNDER PRESSURE.