

DANGER! EXTREMELY FLAMMABLE. VAPOR HARMFUL. CONTENTS UNDER PRESSURE.

1997 CRC Industries, Inc. Warmminster, PA 18974 800-521-3168 (Tech. Info.) 800-272-4620 (Cust. Serv.) All Purpose Enamel Spray Paint Net Wt. 10 oz. (284g)



# All-Purpose Enamel Spray Paint

- Fast Drying
- Indoor/Outdoor Use

### TECHNICAL DATA

Surfaces: Metal, wood, paper and cloth  
 Resin System: Vinyl-toluene oil enamel  
 Heat — 180°F (82°C)  
 Abrasion — good  
 Corrosion — good  
 Solvents — fair  
 VOC COMPLIANT

Task free — 15 to 30 minutes  
 Fully dry — 1 hour  
 Recoat — Within 2 hours or after 24 hours

## Blue Grey 18013



Net Wt. 10 oz. (284g)

**DANGER! EXTREMELY FLAMMABLE.**  
VAPOR HARMFUL. CONTENTS UNDER PRESSURE.  
READ WARNINGS ON BACK PANEL.



97A  
Made in U.S.A.

- DIRECTIONS:** Read entire label before using this product.
1. Shake vigorously for at least one minute after rattling of mixing ball is heard. Shake intermittently during application.
  2. For best results, spray at room temperature (70°F).
  3. Surface to be painted should be clean and dry. Remove dirt, grease, oil, rust, scale and other contaminants.
  4. Mask areas not to be sprayed to protect from overspray.
  5. Hold can 12 to 16 inches from surface. Press spray button firmly. Do not apply with continuous spray. Use back and forth motion, keeping can in a level line with surface.
  6. For best results 3-4 thin coats are recommended rather than one heavy coat. Recoat within 2 hours or after 24 hours.
  7. To prevent valve from clogging after spraying, turn can upside down and press sprayhead for about 3 seconds. This will clean paint from siphon tube and valve. If spray button is clogged, remove from can and run knife edge through tiny slit at end of spray button stem. Clear spray button orifice by inserting pin. Do not insert pins or other sharp objects into valve opening of can.
  8. Coverage: 15 to 20 sq. ft.

**SPECIAL USAGE WARNINGS:**

- Combusts extremely flammable.
- Do not smoke while spraying.
- Extinguish all flames, pilot lights and heaters.
- Do not apply while equipment is energized.
- Vapors will accumulate readily and may ignite. Use only with adequate ventilation.
- Maintain ventilation during use and until all vapors are gone.

**ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Keep away from all electrical sources including battery terminals, electronic components, failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

0 78254 18013 7

5,056,827)

current Material Safety Data Sheet printed on the reverse side of the label. (The CRC system patented under U.S. Patent No. M.S.D. (L)™ is a proprietary label removal

- M.S.D. (L)™ Material Safety Data Label is a Primer for best results
- Use with CRC's All Purpose Enamel Spray
- Use on wood, metal, masonry, and glass
- Resists corrosion, abrasion, fading, and heat
- For contractor applications
- For general use in everyday factory and

To View Emergency M.S.D.S.: Tear (DO NOT CUT) label by running fingernail between perforations. Fold back label. Do not remove until can is empty.

**WARNING:** Contains Acetone 67-64-1, Aliphatic Hydrocarbon 64742-89-8, Xylene 1330-20-7, Aromatic Hydrocarbon 64742-95-6 & Propane/isobutane Mixture 68476-86-8. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Harmful or fatal if swallowed. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Avoid contact with skin or eyes. Overexposure to vapor may cause irritation to eyes, respiratory irritation, headaches, dizziness and nausea. Use with adequate ventilation. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. For skin contact, wash area thoroughly with water. If swallowed, do not induce vomiting. Call a physician. If too much is breathed, remove to fresh air. For severe overexposure call a physician immediately.

**KEEP AWAY FROM CHILDREN**