

To review SDS, Tear (DO NOT CUD) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS) Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y doblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la tara esté vacía.



SAFETY REFLECTIVE PAINT

STEP
2 OF 2

HI-VIZ CLEAR TOP COAT
EASY 2-STEP SYSTEM

Reflects Light Back to Source

Excellent Outdoor Durability



Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

DANGER: EXTREMELY FLAMMABLE.
CAUSES EYE IRRITATION.
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.



No. 18018

Net Wt.
12 oz (340 g)



CRC CLEAR SAFETY REFLECTIVE PAINT

CRC's Reflective Top Coat Paint (Step 2) is designed to be used over CRC's Aluminum Base Coat (Step 1). This coating should be applied as the second step in order to achieve a reflective coating.

DIRECTIONS: Read entire label before using this product.

1. Shake can at least one minute after rattle is heard and occasionally during use.
2. Hold can 6 inches away and spray rapidly onto CRC Aluminum Base Coat to prevent sagging. SPRAY TWO THIN COATS COMPLETELY OVER THE ALUMINUM BASE COAT. DO NOT SPRAY HEAVY COATS AS THIS WILL RESULT IN POOR REFLECTION. Coating will dry in 15-40 minutes depending on temperature and humidity.
3. VERY IMPORTANT: After spraying, turn can upside down and spray 4-5 seconds to clear nozzle/ spray button. Wipe nozzle/ spray button with cloth to prevent clogging. DO NOT REMOVE NOZZLE/ SPRAY BUTTON. If clog occurs due to paint drying, scrap off before reusing.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Suspected of damaging fertility or the unborn child.



Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

Contains dimethyl ether 115-10-6, water 7732-18-5, and propylene glycol monobutyl ether 5131-66-8. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

VOC Category: Flat Paint

MIR Limit: 1.20 (EPA) 0.80 (CA)

©2016 CRC Industries, Inc., 885 Louis Dr, Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Care)
215-442-6260 (SDS)

www.crcindustries.com
Made in U.S.A. 16A

1. Identification

Product identifier: Clear Safety Reflective Paint

Product code 18018

Recommended use Reflective paint

Restrictions None known.

Manufactured or sold by:

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)

Gases under pressure (Liquefied gas)

Health hazards Serious eye damage/eye irritation (Category 2A)

Reproductive toxicity (Category 2)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
dimethyl ether	115-10-6	30 – 40
water	7732-18-5	20 – 30
propylene glycol monobutyl ether	5131-66-8	1 – 3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Drink plenty of water. Do not induce vomiting. In the unlikely event of swallowing contact a physician or poison control center.

Most important symptoms/effects Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Water spray. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media None known.

Specific hazards Flammable or explosive mixtures with air maybe formed. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Many gases are heavier than air and will spread along ground and collect in low or confined areas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spills cannot be contained.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Absorb in vermiculite, dry sand, earth or other absorbent material and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

7. Handling and storage

Handling Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Protect from freezing. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components

dimethyl ether

Type

TWA

Value

1000 ppm

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as nitrile or rubber. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Clear liquid.

Odor Aromatic.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point Not available.

Flash point -2 °F (-19 °C) Tag Closed Cup

Evaporation rate Not available.

Explosive limit - lower (%) 3

Explosive limit - upper (%) 18.6

Vapor pressure 2446 hPa

Vapor density Not available.

Relative density 0.77 – 0.85

Solubility(ies) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

VOC (MIR): 0.37

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products None known.

11. Toxicological information

Information on likely routes of exposure:

Ingestion Expected to be a low ingestion hazard.

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation.

Information on toxicological effects:

Acute toxicity Irritant effects.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity Not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Aspiration hazard Not classified.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions This material must be disposed of as hazardous waste.

Hazardous waste code D001: Waste Flammable liquid

14. Transport information

DOT shipping description UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 None

See full SDS for additional information

16. Other information

Issue date 9/6/2016

Version # 01