

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty.



SAFETY ANTI-SLIP PAINT

YELLOW

Slip Resistant Coating
Long-Lasting Texture

Para obtener información adicional en Español,
visite www.crcindustries.com.

DANGER: EXTREMELY FLAMMABLE.
CAUSES EYE IRRITATION.
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

No. 18025
Net Wt.
12 oz (340 g)



S.D.[L.]
Safety Data Label

APPLICATIONS: For Indoor/ Outdoor use on most surfaces: Stairs, Boat Docks, Ramps, etc. Use as a finish coat and recoat every 2-4 months based on traffic wear. Resistant to oil, gas and most chemicals.

DIRECTIONS: Read entire label before using this product.

1. Surface must be dry, clean and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when temperature is between 50° and 90° F (10° and 32° C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray with steady strokes at a distance of 6 to 10 inches (15 to 25 cm). Several light coats give a better finish than one heavy coat. Tack free in 60 minutes and fully cured in 24 hours.
4. If clogging develops, turn sprayhead ¼ turn and spray or remove and clean sprayhead. DO NOT use a pin or place anything into the can opening. With can and sprayhead pointed away, re-insert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Please recycle empty cans. Dispose of partially used cans responsibly according to local regulations. DO NOT incinerate or compact.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.



Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

Contains acetone 67-64-1, propane 74-98-6, hydrotreated light distillates 64742-47-8, n-butane 106-97-8, toluene 108-88-3, ethylene glycol propyl ether 2807-30-9, propylene glycol methyl ether acetate 108-65-6, titanium dioxide 13463-67-7, C.I. Pigment Yellow 194 82199-12-0, and polyethylene 9002-88-4. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

VOC Category: Slip-Resistant Coating **MIR Limit: 2.45 (EPA) 2.10 (CA)**

©2016 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical Info) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS)

Made in U.S.A. 16A
www.crcindustries.com



WARNING: This product can expose you to titanium dioxide, which is known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

1. Identification

Product identifier: Yellow Safety Anti-Slip Paint

Product code 18025

Recommended use Slip-resistant paint

Restrictions None known.

Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)

Gases under pressure (Liquefied gas)

Health hazards Serious eye damage/eye irritation (Category 2A)

Carcinogenicity (Category 2)

Reproductive toxicity (Category 2)

Specific target organ toxicity, single exposure

(Category 3 narcotic effects)

Specific target organ toxicity, repeated exposure (Category 2)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
acetone	67-64-1	30 – 40
propane	74-98-6	10 – 20
hydro-treated light distillates	64742-47-8	5 – 10
n-butane	106-97-8	5 – 10
toluene	108-88-3	5 – 10
ethylene glycol propyl ether	2807-30-9	3 – 5
propylene glycol methyl ether acetate	108-65-5	3 – 5
titanium dioxide	13463-67-7	3 – 5
C.I. Pigment Yellow 194	82199-12-0	1 – 3
polyethylene	9002-88-4	1 – 3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Drink plenty of water. Do not induce vomiting.

Most important symptoms/effects Severe eye irritation. Narcotic effects.

Special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Water spray. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards Extremely flammable aerosol. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Many vapors are heavier than air and will spread along ground and collect in low or confined areas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Absorb in vermiculite, dry sand, earth or other absorbent material and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

7. Handling and storage

Handling Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not breathe gas, mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Protect from freezing. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
acetone	TWA	250 ppm
propane	PEL	1000 ppm
titanium dioxide	TWA	10 mg/m ³
n-butane	STEL	1000 ppm
toluene	TWA	20 ppm
polyethylene	TWA	5 mg/m ³

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as nitrile or rubber. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Yellow liquid.

Odor threshold Not available.

Melting point/freezing point -139 °F (-95 °C)

Flash point < -2 °F (< -19 °C) Tag Closed Cup

Explosive limit - lower (%) 1.7

Vapor pressure 2126 hPa

Relative density 0.77 – 0.85

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 410 °F (210 °C)

Decomposition temperature Not available.

VOC (MIR): 1.01

Odor Aromatic.

pH Not available.

Initial boiling rate 133 °F (56 °C)

Evaporation rate Fast.

Explosive limit - upper (%) 10.9

Vapor density > 1 (air = 1)

Solubility(ies) Not available.

Viscosity Not available.

10. Stability and reactivity

Reactivity Non-reactive

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine. Acids.

Hazardous decomposition products None known.

Chemical stability Stable

11. Toxicological information

Information on likely routes of exposure:

Ingestion May cause vomiting, diarrhea or gastrointestinal discomfort.

Inhalation May cause drowsiness, dizziness, headache, nausea and vomiting. May cause damage to organs through prolonged or repeated exposure by inhalation.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Causes serious eye irritation.

Information on toxicological effects:

Acute toxicity Severe eye irritation. Narcotic effects.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity Suspected of causing cancer.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Aspiration hazard Not an aspiration hazard.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions This material must be disposed of as hazardous waste.

Hazardous waste code D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 ethylene glycol propyl ether, toluene

See full SDS for additional information

16. Other information

Issue date 9/6/2016

Version # 01