

WARNING: Contains Acetone 67-64-1, Toluene 108-88-3, Xylene 1380-20-7, Ethylbenzene 100-41-4, Methyl Isobutyl Ketone 108-10-1, Dimethyl Ether 115-10-6, Propane 74-98-0 and acetone 75-28-5. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is extremely flammable and should be kept from all flames and other ignition sources. Harmful or fatal if swallowed. This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm. Reports have associated repaired and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Avoid contact with skin or eyes. Overexposure to vapor may cause irritation to eyes, respiratory irritation, headaches, dizziness and nausea. Use with adequate ventilation. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. For skin contact, wash area thoroughly with water. If swallowed, do not induce vomiting. Call a physician. If too much is breathed, remove to fresh air. For severe overexposure call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product. **KEEP AWAY FROM CHILDREN.**

To view Emergency M.S.D.S.: Tear (DO NOT CUT) label by running fingernail between perforations. Fold back label. Do not remove until can is empty.

DIRECTIONS: Read entire label before using this product. Shake vigorously for at least one minute after rattling of mixing ball is heard. Shake intermittently during application.

- For best results, spray at room temperature (70°F).
- Do not use sharp object to remove overcap.
- Surface to be painted should be clean and dry. Remove dirt, grease, oil, rust, scale and other contaminants.
- Mask areas not to be sprayed to protect from overspray.
- Hold can 6 to 10 inches from surface. Press spray button firmly. Do not apply with continuous spray. Use back and forth motion, keeping can in a level line with surface.
- For best results 2-4 thin coats are recommended rather than one heavy coat. Recoat within one hour.
- To prevent valve from clogging after spraying, turn can upside down and press sprayhead for about 3 seconds. This will clean paint from siphon tube and valve. If spray button is clogged, remove from can and run knife edge through tiny slit at end of spray button stem. Clean spray button opening of can.
- Coverage: 35 to 40 sq. ft.

9. To prevent valve from clogging after spraying, turn can upside down and press sprayhead for about 3 seconds. This will clean paint from siphon tube and valve. If spray button is clogged, remove from can and run knife edge through tiny slit at end of spray button stem. Clean spray button opening of can.

SPECIAL USAGE WARNINGS:

- Contents extremely flammable.
- Do not smoke while spraying.
- Extinguish all flames, pilot lights and heaters.
- Do not apply while equipment is energized.
- Do not contact with skin or eyes.
- Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

ALL USED AND WASHED PRODUCT SHOULD BE DISPOSED OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

- Use on all metal surfaces for corrosion control.
- Recommended for moderate to severe corrosive environments.
- Formulated to resist rusting, peeling, and fading.
- Use with CRC's Rust Proof Enamel Spray Primer for best results.
- M.S.D.S. ("Material Safety Data Sheet") is a current Material Safety Data Sheet printed on the reverse side of the label. (The CRC M.S.D.S. ["MSDS"] is a proprietary label removal system patented under U.S. Patent No. 5,056,027).



02A
Made in
Canada



Enclosure Gray 18115



DANGER! EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED, VAPOR HARMFUL. EYE & SKIN IRRITANT. CONTENTS UNDER PRESSURE.
HEAD WARNING: 963 ON BACK PANEL

Net Wt. 15 oz. (425g)

TECHNICAL DATA

Surfaces: Metal, Wood
 Resin System: Acrylic enamel
 Reapplication: Fully dry — 1 hour
 Recoat: Within 1 hour
 Heat: 200°F (149°C)
 Adhesion — Good
 Corrosion — excellent
 Solvents — excellent

Dry Time:
 Tack-free — 15 to 20 minutes
 Fully dry — 1 hour
 Recoat — Within 1 hour

Other Features:
 • Will not flare.
 • VOC COMPLIANT

Rust Proof Enamel
 Spray Paint
 Part # 18115
 Net Wt. 15 oz. (425g)
 www.crcindustries.com

©2002 CRC Industries, Inc.
 Warminster, PA 18974
 800-521-2108 (Tech. Serv.)
 800-272-0820 (Cust. Serv.)
 215-442-8200 (MSDS)

DANGER! EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED, VAPOR HARMFUL, EYE & SKIN IRRITANT. CONTENTS UNDER PRESSURE.



Rust Proof Enamel

Spray Paint

- Durable, Fights Corrosion
- Resists Rusting, Peeling & Fading
- High Solids Formula