



# Upside Down Marking Spray Paint

## FLUORESCENT ORANGE

**Bright, Vivid Lines**  
**Won't Wash Away**  
**Won't Harm Grass**

### Technical Data

**Applications:** Utility Marking, Construction Sites, Surveying, Mining  
**Resin System:** Alkyd  
**Dry Time:** 15 Minutes to Touch  
**Gloss:** Flat

Meets APWA Color Standards • VOC Compliant • Non-Clog Nozzle

Para obtener información adicional en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

**DANGER:** EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN. Read warnings on back panel.



**No. 18208**

**Net Wt.**  
**1 lb 1 oz (481 g)**



## CRC Upside Down Marking Spray Paint

**DIRECTIONS:** Read entire label before using this product.

- For best results, use when can temperature is between 40°F and 90°F (4°C and 32°C).
- Shake can at least one minute after rattle is heard and occasionally during use.
- Invert can and hold 4 to 6 inches (10 to 15cm) above surface to be marked. Press sprayhead to the side to actuate.
- If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
- To clear sprayhead for future use, turn can right side up and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

### Danger

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.



### Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose or store at temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national/international regulations.

### First Aid

If swallowed: Call a physician/poison center immediately. Do NOT induce vomiting.

### Ingredients

Contains calcium carbonate 1317-65-3, propane 74-98-6, light aliphatic solvent naphtha 64742-89-8, n-butane 106-97-8, hydrotreated light distillates 64742-47-8, and isobutyl acetate 110-19-0.

Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

### Electrical Shock Hazard

This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

**VOC Category:** Ground Traffic and Marking Coatings | **MIR Limit:** 1.20 (EPA) 0.85 (CA)

©2016 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974 | Made in U.S.A. 16A  
800-521-3168 (Technical Info) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS) | [www.crcindustries.com](http://www.crcindustries.com)



**WARNING:** This product can expose you to ethylbenzene which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## 1. Identification

**Product identifier:** Upside Down Marking Paints-Fluorescent Orange

**Product code** 18208

**Recommended use** Coating

**Restrictions** None known.

**Manufactured by:** CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

**Phone:** 215-674-4300

**Emergency phone number** CHEMTREC - 24 HOURS: 800-424-9300

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols (Category 1)  
Gases under pressure (Liquefied gas)

**Health hazards** Aspiration hazard (Category 1)

**Label elements (see front side of label)**

## 3. Composition/information on ingredients

**Hazardous components**

Chemical name	CAS number	%
calcium carbonate	1317-65-3	10 – 20
propane	74-98-6	10 – 20
light aliphatic solvent naphtha	64742-89-8	10 – 20
n-butane	106-97-8	5 – 10
hydrotreated light distillates	64742-47-8	3 – 5
isobutyl acetate	110-19-0	3 – 5

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

## 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Take off contaminated clothing and wash before reuse. Get medical attention if irritation develops and persists.

**Eye contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Ingestion** Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

**Most important symptoms/effects** Direct contact with eyes may cause temporary irritation.

**Special treatment needed** Provide general supportive measures and treat symptomatically.

## 5. Fire-fighting measures

**Suitable extinguishing media** Powder. Water spray. Carbon dioxide (CO2). Dry sand. Alcohol resistant foam.

**Unsuitable extinguishing media** None known.

**Specific hazards** Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

**Special protective equipment and precautions for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures

**Personal precautions** Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

**Containment and cleaning up** Eliminate all ignition sources. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

## 7. Handling and storage

**Handling** Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

**Storage** Store locked up. Store in a well-ventilated place. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F.

## 8. Exposure controls/personal protection

**Occupational exposure limits**

Components	Type	Value
Calcium carbonate	PEL	5 mg/m3
Isobutyl acetate	TWA	150 ppm
Propane	TWA	1000 ppm
n-Butane	TWA	1000 ppm

**Appropriate engineering controls** Mechanical ventilation or local exhaust ventilation is recommended.

**Individual protection measures:**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection** Wear protective gloves such as nitrile or rubber.

**Respiratory protection** If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies.

## 9. Physical and chemical properties

**Appearance** Orange liquid.

**Odor** Aromatic.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -146 °F (-99 °C)

**Initial boiling point** -47 °F (-44 °C)

**Flash point** -2 °F (-19 °C)

**Evaporation rate** Not available.

**Explosive limit - lower (%)** 1.7

**Explosive limit - upper (%)** 10.9

**Vapor pressure** 2148 hPa

**Vapor density** > 1 (Air = 1)

**Relative density** 0.77 – 0.85

**Solubility(ies)** Not available.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** 410 °F (210 °C)

**Decomposition temperature** Not available.

**Viscosity** Not available.

**MIR Value:** 0.57

## 10. Stability and reactivity

**Reactivity** Non-reactive

**Chemical stability** Stable

**Possibility of hazardous reactions** No

**Conditions to avoid** Heat, flames and sparks. Incompatible materials.

**Incompatible materials** Strong oxidizing agents. Acids. Fluorine. Chlorine. Nitrates.

**Hazardous decomposition products** None known.

## 11. Toxicological information

**Information on likely routes of exposure:**

**Ingestion** May be fatal if swallowed and enters airways.

**Inhalation** May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful.

**Skin contact** Prolonged skin contact may cause temporary irritation.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Information on toxicological effects:**

**Acute toxicity** May be fatal if swallowed and enters airways.

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** Not expected to cause skin sensitization.

**Carcinogenicity** Not expected to be hazardous by OSHA criteria.

**Aspiration hazard** May be harmful if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

See full SDS for additional information

## 13. Disposal considerations

**Disposal instructions** This material must be disposed of as hazardous waste.

**Hazardous waste code** D001: Waste Flammable liquid

## 14. Transport information

**DOT shipping description:** UN1950, Aerosols, flammable, 2.1, limited quantity

## 15. Regulatory information

California Prop 65 Ethylbenzene

See full SDS for additional information

## 16. Other information

**Issue date** 8/8/2016

**Version #** 02