

WARNING: Contains Aliphatic Hydrocarbon 6472-82-89-8, Xylene 1330-20-7 & Propane/isobutane Mixture 68476-86-8. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Harmful or fatal if swallowed. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Avoid contact with skin or eyes. Overexposure to vapor may cause irritation to eyes, respiratory irritation, headaches, dizziness and nausea. Use with adequate ventilation. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. For skin contact, wash area thoroughly with water. If swallowed, do not induce vomiting. Call a physician. If too much is breathed, remove to fresh air. For severe overexposure call a physician immediately.

KEEP AWAY FROM CHILDREN

To view Emergency M.S.D.S.: Tear (DO NOT CUT) label by running fingernail between perforations. Fold back label. Do not remove until can is empty.

- Use on concrete, asphalt, gravel and wood
- One can covers approximately 290 linear feet of crisp 3/2 inch line
- Resists water, oil, UV rays, gasoline and most solvents
- Use with CRC Striping Equipment for uniform application
- M.S.D. (L.)™ ("Material Safety Data Label" is a current Material Safety Data Sheet printed on the reverse side of the label. (The CRC M.S.D. (L.)™ under U.S. Patent No. 5,056,827)



97A
Made in
U.S.A.

ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

SPECIAL USAGE WARNINGS:

- Contents extremely flammable.
- Do not smoke while spraying.
- Extinguish all flames, pilot lights and heaters.
- Do not apply while equipment is energized.
- Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

- DIRECTIONS:** Read entire label before using this product.
1. Shake can well. After you hear the rattle of mixing ball, continue to shake the can for one minute.
 2. Turn can upside down and place in the can holder of the 4-way paint stripper machine or multi-purpose striping stick.
 3. Adjust for proper line width (2-5") by raising or lowering the handle of the 4-way paint stripper.
 4. If striping is interrupted, shake the can again for 10 seconds before resuming striping.
 5. After use, to prevent sprayhead from clogging, hold can upright, away from face and eyes, and depress nozzle.
 6. May be used at temperatures as low as 35°F. Store can at temperatures between 60°F and 80°F.



Striping & Traffic

Spray Paint

- Durable, One Coat Coverage
- For Heavy Traffic Areas
- High Solids Formula

TECHNICAL DATA

- Surfaces:** Concrete, asphalt or gravel
Applications: Parking lots, warehouse loading areas, factories, etc.
Resin System: Alkyd enamel
Dry Time: Touch dry — 2 to 5 minutes
Resistance: Weather — excellent
 Abrasion — excellent
Valve: Unique valve sprays more direct, minimizing overspray.
- Other Features:**
- Formulated for heavy traffic areas
 - One coat coverage
 - Squeeze cap prevents accidental discharge
 - Non-clogging nozzle
 - Bright vivid lines
- VOC COMPLIANT**
 Max. VOC 66%

Black 18304



Net Wt. 18 oz. (510g)

DANGER! EXTREMELY FLAMMABLE.
 VAPOR HARMFUL. CONTENTS UNDER PRESSURE.
 READ WARNINGS ON BACK PANEL.

©1997 CRC Industries, Inc.
 Warmminster, PA 18974
 800-521-3168 (Tech. Inro.)
 800-272-4620 (Cust. Serv.)
 Net Wt. 18 oz. (510g)
 Part # 18304
 Spray Paint
 Striping & Traffic

DANGER! EXTREMELY FLAMMABLE. VAPOR HARMFUL.
 CONTENTS UNDER PRESSURE.