DOUBLE MONEY BACK GUARANTEE

INSTANT • PERMANENT

COOLING SYSTEM STOP LEAK

ELIMINADOR DE FUGAS PARA
EL SISTEMA DE REFRIGERACIÓN

ONE-STEP REPAIR
JUST POUR & GO

PERMANENTLY FIXES:

RADIATORS
HEAD GASKETS
ENGINE BLOCKS
HEATER CORES
FREEZE PLUGS

EXCEEDS ASTM D3147
WON'T CLOG COOLING SYSTEMS

WARNING:
CAUSES EYE IRRITATION.
READ WARNINGS ON BACK PANEL.

No. 401214 15 fl oz (444 mL)

INSTANT • PERMANENT

COOLING SYSTEM STOP LEAK

Las instrucciones Españolas adentro →

WARNING: Contains water 7732-18-5, polyalkylene glycol 9038-95-3, sodium silicate 1344-09-8, aluminosilicate fibers 142844-00-6 and cellulose 9004-34-6. Avoid contact with skin and eyes. Wear gloves and safety glasses. Wash thoroughly after handling. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use. If you experience any symptoms listed on this label, increase ventilation or leave the area. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. See physician if irritation persists. If too much is breathed, remove to fresh air. If swallowed, rinse mouth. Call a poison center/doctor if you feel unwell. For additional information, consult SDS for this product.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water.

KEEP AWAY FROM CHILDREN

DOUBLE MONEY-BACK GUARANTEE: Call CRC Customer Care at 800-272-8963 or visit crcindustries.com for details.

©2015 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical Info)
800-272-8963 (Customer Care)
215-442-6260 (SDS)
www.crcindustries.com
Made in U.S.A. CRC#890A
15A

0 78372 01214 3

OPEN

ELIMINADOR INSTANTÁNEO Y PERMANENTE DE FUGAS PARA EL SISTEMA DE REFRIGERACIÓN

ADVERTENCIA: Contiene agua 7732-18-5, polialquilenglicol 9038-95-3, silicato de sodio 1344-09-8, fibras de aluminosilicato 142844-00-6 y celulosa 9004-34-6. Evite el contacto con los ojos y la piel. Use guantes y gafas protectoras. Lavarse completamente luego de manipular el material. Usar con ventilación adecuada. Abra las puertas y las ventanas o utilice otros medios para asegurar el suministro de aire fresco durante el uso. Si nota cualquiera de los síntomas indicados en ésta etiqueta, aumente la ventilación o aléjese del área. El abuso deliberado concentrando e inhalando el contenido es ilegal y puede ser nocivo o fatal. El abuso de inhalación puede causar la muerte. Este producto contiene productos químicos que de acuerdo con el Estado de California producen cáncer y defectos de nacimiento u otros daños reproductivos.

PRIMEROS AUXILIOS: Si entra en contacto con los ojos o la piel, enjuáguelos con agua durante 15 minutos. Consulte con un médico si persiste la irritación. Si se inhala demasiado, dirigirse al aire libre. Si lo traga, enjuáguese la boca. Llame al Centro de envenenamiento o a un médico si no se siente bien. Por mayor información, consulte el SDS de este producto.

DESECHO: Todo el producto utilizado y sobrante deberá desecharse de acuerdo con las normas nacionales, estatales y locales. No los vierta en desagües, rejillas de piso, en el suelo o en un lago o arroyo.

MANTENER ALEJADO DEL ALCANCE DE LOS NIÑOS

SI NO QUEDA SATISFECHO LE DEVOLVEMOS EL DOBLE DE SU DINERO: Llame al Servicio al cliente de CRC al 1800-272-8963 o visite crcindustries.com por más detalles.

HINGE AREA

Instantly and permanently fixes leaks in all types of water-cooled engines. Repairs radiators, cracked heads & blocks, head gaskets, heater cores and water pumps. JUST POUR IN AND GO! Compatible with all types of antifreeze and coolant.

DOSAGE: One bottle treats cooling systems up to 5 gallons/20 quarts. For larger vehicles, use two bottles. For smaller cooling systems, add 1/2 bottle making sure the contents are well mixed first. For a more complete job, clean/flush the cooling system with **K&W 7 Minute Rapid Flush** prior to adding the product.

DIRECTIONS: ***Read entire label before using product.*** For cooling systems up to 20 quarts capacity (cars, passenger trucks, vans).

1. With engine off and cooled, remove radiator cap. **2.** Shake bottle vigorously for 30 seconds. **3.** Pour entire contents into car or light truck radiator. DO NOT pour directly onto radiator core/fins. **4.** Replace radiator cap and run engine up to operating temperature until leak stops.

Repara de forma instantánea y permanente las fugas en todo tipo de motores refrigerados por agua. Repara radiadores, cabezales y bloques rajados, juntas de tapas de cilindros, núcleos de calefactor y bombas de agua. ¡SIMPLEMENTE VIÉRTALO Y LISTO! Compatible con todo tipo de anticongelante y refrigerante.

DOSIS: Una botella trata sistemas de refrigeración de hasta 5 galones / 20 litros. Para vehículos más grandes, use dos botellas. Para sistemas refrigerantes más pequeños, use 1/2 botella verificando que el contenido esté bien mezclado. Para un trabajo más completo, limpie/enjuague el sistema de refrigeración con Limpieza rápida de 7 minutos de K&W antes de agregar el producto.

INSTRUCCIONES: ***Lea toda la etiqueta antes de usar este producto.*** Para sistemas de refrigeración de hasta 20 litros de capacidad (autos, camiones de pasajeros, camionetas).

1. Con el motor apagado y frío, quite la tapa del radiador. **2.** Agite bien la botella por 30 segundos. **3.** Vierta todo el contenido dentro del radiador del auto o de la camioneta. NO lo vierta directamente dentro del núcleo/aletas del radiador. **4.** Vuelva a colocar la tapa del radiador y haga funcionar el motor a la temperatura de trabajo hasta que se detenga la fuga.

HINGE AREA