



**KNOCK'ER® LOOSE  
PENETRANT**



KNOCK'ER® LOOSE loosens rusted and corroded nuts, bolts, couplings, fittings, hinges and frozen components. Specially formulated to dissolve rust, varnishes, gums, and corrosion. Lubricating residue prevents corrosion and displaces water.

**DIRECTIONS:** Read entire label before using this product.

1. Spray directly on corroded fasteners.
2. Allow oil to seep between joints and surface area.
3. Tap joints lightly to aid process.
4. Loosen or remove fastener.
5. If necessary, repeat steps 1-3 until fastener breaks free.
6. Severely frozen or welded fasteners may require the help of a power tool or nut cracker to loosen.
7. Do not apply while equipment is energized.

**WARNING:** Contains Petroleum Distillate 8052-41-3, Petroleum Distillate 64742-47-8, Octadecanoic Acid 112-80-1, and Carbon Dioxide 124-38-9. Do not puncture, incinerate, or store can above 120°F. Exposure to high temperature may cause bursting. Do not place in direct sunlight or near any heat source.

Product is flammable and should be kept from all flames and other ignition sources. Use only in a well ventilated area. Overexposure to vapor may cause irritation of the eyes and cause headaches and nausea. Deliberate misuse by concentrating and inhaling the mist contents can be harmful or fatal. Inhalation of the mist may cause irritation of the upper respiratory tract and breathing problems. **FIRST AID:** In case of eye contact, flush with large amounts of water for at least 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately. **Disposal:** All used and unused product should be disposed of in accordance with all local, state and federal regulations. **EMPTY** containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. **DO NOT DUMP INTO SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER.**

**ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

For additional information, consult the Material Safety Data Sheet for this product.

**KEEP AWAY FROM CHILDREN**

**Modo de empleo:** Lea la etiqueta completa antes de usar.

1. Rocíar, directamente, los sujetadores corroidos.
2. Permitir que el aceite se filtre entre las juntas y la superficie.
3. Golpear suavemente la juntas para ayudar al proceso.
4. Aflojar o remover los sujetadores.
5. De ser necesario, repetir los pasos 1-3 hasta que los sujetadores están libres.
6. Los sujetadores que están severamente atascados o soldados podrían necesitar la ayuda de una herramienta de poder o un cascanueces para ser aflojados.
7. No aplique mientras el equipo está activado.

**MANTÉNGASE LEJOS DEL ALCANCE DE LOS NIÑOS**



**Technician  
Grade**

**KNOCK'ER®  
LOOSE  
PENETRANT**

**Super Penetrating Formula**

**Dissolves Rust and Corrosion**

**Lubricates and Prevents Rust**

Net Wt. 9 oz. (255 g)

No. 401712

**DANGER: FLAMMABLE, HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.**



©2003 CRC Industries, Inc.  
Warminster, PA 18974  
800-321-3168 Technical Information  
800-272-8965 Customer Service  
215-442-6260 (MSDS)  
www.crcindustries.com

Made in U.S.A.  
CRC457SE  
03A