



Trans-X® Posi-Trac® Limited Slip Gear Oil Additive is designed to prevent chattering differentials and improve gear oil performance.

- Quiets noisy gears
- Mixes with any gear oil

Recommended for use in limited slip, positraction and standard differentials. Should be used with conventional GL-5 or synthetic gear oils. Not for use in automatic transmissions or other ATF applications. Not for use in Jeeps® with Quadra-Trac® or Quadra-Drive®.*

DIRECTIONS: Please read entire label before using this product. 1. Drain differential while warm. 2. Add entire contents of tube to differential. 3. Fill differential with manufacturers recommended gear oil. 4. Do not overtighten.

WARNING: Contains Petroleum Distillates 64742-53-6 and 64742-52-5, Long Chain Alcohol 800967-5520P, Alkyl phosphate ester, Amine salt 800967-5546P, Alkenyl Phosphate 800967-5199P, Mineral oil 64742-54-7. This product contains chemicals known to the state of California to cause cancer, birth defects, and other reproductive harm. Keep away from heat or flame. Avoid contact with skin and eyes.

FIRST AID: In case of eye or skin contact, flush with large amounts of water for at least 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.

KEEP OUT OF REACH OF CHILDREN.

DISPOSAL: All product should be disposed of in accordance with all local, state and federal regulations.

For additional information consult the Material Safety Data Sheet for this product.

El aditivo para diferenciales de carrera limitada, Trans-X® Posi/Trac®, está diseñado para prevenir el traqueteo de los diferenciales y mejorar el rendimiento del aceite para engranajes.

- Silencia el ruido de los engranajes
- Se mezcla con cualquier aceite para engranajes

Recomendado par uso en diferenciales de deslizamiento controlado, diferencial estándar y de tracción. Debe ser usado con aceites de engranajes convencionales de nivel GL-5 o aceites de engranajes sintéticos. No se debe usar en transmisiones automáticas u otras aplicaciones de ATF. Tampoco se puede usar en Jeeps con Quadra-Trac o Quadra-Drive.*

MODO DE EMPLEO: Por favor lea la etiqueta completamente antes de usar el producto. 1. Drene el diferencial cuando esté caliente. 2. Añada al diferencial, el contenido completo de la lata. 3. Llene el diferencial con el aceite para engranaje recomendado por el fabricante.

MANTENGA LEJOS DEL ALCANCE DE LOS NIÑOS.

DESECHO: Todo el producto usado o no debe desecharse de acuerdo a las leyes locales, regionales y federales.

Para información adicional consulte la Hoja de Datos de Seguridad de este producto.



©2008 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical Info)
800-272-8963 (Customer Service)
215-442-6260 (MSDS)

www.crcindustries.com
Made in U.S.A.
CRC#914A
08A



**Prevents Chattering,
Jerking & Slipping**

TRANS-X®
"Mechanic In A Can"

POSI-TRAC®

**LIMITED SLIP GEAR
OIL ADDITIVE
ADITIVO DEL ACEITE
DEL ENGRANAJE**

**SUITABLE FOR USE IN OEM LIMITED
SLIP DIFFERENTIAL APPLICATIONS**

GM #1052358

FORD #M2C118-A

CHRYSLER #4318060

AND MOST IMPORTS



7 fl. oz. (207 mL)

No. 402508

Read Warnings on back panel.