

SUPER TURBO® Formula Engine Oil Stop Leak

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

Specially designed to rejuvenate worn or aged front and rear seals, valve cover gaskets, pan gaskets, timing gear gaskets and other seals found in today's high tech engines. Ideal for cars, trucks, boats or heavy duty equipment. Suitable with all motor oils, gasoline or diesel engines.

DIRECTIONS: *Read entire label before using this product.*

With motor off, pour entire contents into engine oil. Do not overfill. Seals and gaskets that continue to leak after 500 miles of driving most likely require mechanical replacement.

WARNING: Contains Hydrotreated naphthenic oil 64742-53-6, 64742-52-5 and Alkoxy heterocyclic ether additive blend. **FIRST AID:** In case of eye contact, flush with plenty of water for 15 minutes. Seek medical attention. For skin contact, wash thoroughly. If swallowed, DO NOT induce vomiting; give large quantities of water. Call a physician immediately.

KEEP AWAY FROM CHILDREN.

Disposal: All used and unused product should be disposed of in accordance with local, state, and federal regulations. DO NOT dump in sewers, floor drains, on the ground, or into any body of water. For additional information, consult MSDS for this product. **Professional users should follow all applicable OSHA regulations.**

La formula del Super Turbo® Engine Oil Stop Leak (producto para detener las fugas de aceite del motor) esta diseñada especialmente para restaurar los sellos frontales y traseros viejos, los empaques de la tapa para punterías, los empaques del cárter o cigüeñal, los empaques de la tapa para distribución, y otros sellos que se encuentran en los motores modernos de alta tecnología. Ideal para los automóviles, camiones, botes o equipo de trabajo pesado. Se recomienda en cualquier aceite de motor, motores de gasolina o diesel.

MODO DE EMPLEO: *Lea la etiqueta antes de usar este producto.*

Con el motor apagado, vierta el contenido entero dentro del aceite del motor. No llene de más. Si las fugas de los sellos y empaques continúan después de conducir durante 500 millas, seguramente es necesario un reemplazo mecánico.

#402715



©2010 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 Technical Information
800-272-8963 Customer Service
215-442-6260 (MSDS)
www.crcindustries.com
Made in U.S.A.
10A CRC#904A



**SUPER
TURBO®**



**Stops
Oil
Leaks
Fast!**

ENGINE OIL STOP LEAK

**RESTORES AND RECONDITIONS
SEALS AND GASKETS**

**RESTAURA Y RECONDICIONA
LOS SELLOS Y EMPAQUES**

CAREFULLY READ WARNINGS ON BACK PANEL.

NET WT. 15 FL. OZ. 444 mL

No. 402715