

AVIEX®

DIESEL FUEL CONDITIONER WITH ANTI-GEL

Nature can put a real strain on your hard-working truck's fuel system, hinder performance and put your engine at risk. That's why there's AVIEX® Diesel Fuel Conditioner with Anti-Gel. Just pour it in to provide your truck's engine with increased lubricity, clean injectors, increased performance and multifunctional protection against extreme weather conditions. Guards against such things as: wax formation, corrosion, low fuel economy and power and fuel line and filter icing. Decreases emissions and particulates while improving fuel economy.

TREATMENT: Read entire label before using this product. For preventive maintenance or To lower pour point by as much as 15°F and CFPP by 24°F:

- One quart treats 125 gallons of fuel
- One gallon treats 500 gallons of fuel. Five gallons treats 2500 gallons of fuel.
- To lower pour point by as much as 35°F and CFPP by 31°F:
 - One quart treats 50 gallons of fuel.
 - One gallon treats 200 gallons of fuel.
 - Five gallons treats 1000 gallons of fuel.

To reliquify gelled fuel:

1. Remove diesel fuel filter. 2. Fill removed or new filter with AVIEX® Diesel Fuel Conditioner with Anti-Gel. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until fuel power is restored to engine.

AVIEX®

DIESEL FUEL CONDITIONER WITH ANTI-GEL

- **IMPROVES FUEL ECONOMY & POWER**
- **REDUCES EXHAUST AND EMISSIONS**
- **LOWERS POUR POINT**
- **RELIQUEFIES GELLED FUEL**
- **LUBRICATES VITAL PARTS**

Net Weight: 35.3 lbs. (16 Kg) Part No. 405005

DANGER: COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED. Read warnings on side panel.

Storage of this container outside will cause this label to become illegible.

AVIEX®

WARNING: Contains Petroleum Distillate 68476-34-6, Copolymer ester NJRT 800967-5483P, Light Aromatic petroleum naphtha 64742-95-6, Mineral Oil 64742-53-6, Heavy Aromatic Naphtha 64742-94-5, Polyolefin amide alkeneamine NJRT 800967-5478P. Overexposure to vapor may cause eye and skin irritation, irritation to respiratory tract, headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. Product is combustible and should be kept from all flames and other ignition sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use only in a well ventilated area. Avoid continuous breathing of vapors. Avoid contact with skin and eyes.

FIRST AID: In case of eye contact, flush with water for 15 minutes. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.

KEEP AWAY FROM CHILDREN

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Do not cut or weld containers due to explosive hazard. **FOR SPILLS,** use proper protective equipment. Take precautions as necessary to prevent contamination of surface or ground waters. For small spills, use absorbent and sweep into closed containers for disposal. For large spills evacuate the area, dike and transfer into containers for disposal.

DISPOSAL: Unused contents and containers must be disposed of in accordance with all federal, state and local regulations. EMPTY containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. **DO NOT DUMP INTO SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER.**

For additional information, consult the Material Safety Data Sheet for this product.



©2000 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 Technical Information
800-272-8963 Customer Service
215-442-6262 (MSDS)
www.crcindustries.com

CHC4637J
Made in U.S.A.
00A