

ALL SEASON PERFORMANCE • ALL SEASON PROTECTION



# XELIX

## DIESEL FUEL CONDITIONER

and ONE SHOT INJECTOR CLEANER

- STABILIZES FUEL
- REDUCES EXHAUST EMISSIONS
- IMPROVES FUEL ECONOMY AND POWER
- PROTECTS AGAINST CORROSION
- LUBRICATES VITAL PARTS

Part No. 405128  
Old Part No. 5128  
Net Contents: 128 fl. oz. (1 GALLON) 3.78 L

**DANGER:** HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.  
Read warnings on back panel.

## AVIEX® DIESEL FUEL CONDITIONER AND ONE SHOT INJECTOR CLEANER

Get the most out of your hard working truck. Put the power of AVIEX® Diesel Fuel Conditioner and One Shot Injector Cleaner to work for you. Get the added engine performance you need to keep your rig running strong - all season long. Just pour it in to add lubricity and restore cleanliness to your entire fuel injection system in one quick and easy application.

**TREATMENT:** Read entire label before using this product. For preventative maintenance: This container is sufficient to treat up to 500 gallons of diesel fuel, depending on fuel temperature.

To reliquefy gelled fuel: 1. Remove diesel fuel filter. 2. Fill removed or new filter with AVIEX® Diesel Fuel Conditioner and One Shot Injector Cleaner. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until full power is restored to engine.

For pre-existing conditions, use 1 gallon to 200 gallons of fuel. Pour into fuel tank and operate normally.

For anticipated extreme conditions, add AVIEX® Premium Anti-Gel with Lubricity (405528) to fuel prior to temperature drop.

**WARNING:** Contains Petroleum Distillate 68476-34-6, 1,2,3,5 Tetramethyl benzene 627-53-7, Alkylbenzene NJRT 800967-5503P, Heavy Aromatic Naphtha 64742-94-5 and Polyolefinamide alkeneamine NJRT 800967-5478P. Overexposure to vapor may cause eye and skin irritation, irritation to respiratory tract, headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. Product is combustible and should be kept from all flames and other ignition sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use only in a well ventilated area. Avoid continuous breathing of vapors. Avoid contact with skin and eyes.

**FIRST AID:** In case of eye contact, flush with water for 15 minutes. For skin contact, wash with soap and water. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.


KEEP AWAY FROM CHILDREN

**HANDLING AND SPILL PRECAUTIONS:** Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Do not cut or weld containers due to explosive hazard. FOR SPILLS, use proper protective equipment. Take precautions as necessary to prevent contamination of surface or ground waters. For small spills, use absorbent and sweep into closed containers for disposal. For large spills evacuate the area, dike and transfer into containers for disposal.

**DISPOSAL:** Unused contents and containers must be disposed of in accordance with all federal, state and local regulations. EMPTY containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimers. DO NOT DUMP INTO SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER.

For additional information, consult the Material Safety Data Sheet for this product.

- Cleans Injectors
- Increases MPG
- Maintains Cetane Rating
- Prevents Corrosion
- Reduces Emissions
- Reliquefies Gelled Fuel



©2000 CRC Industries, Inc. CRC 606H  
Warminster, PA 18974. Made in U.S.A.  
800-521-5168 Technical Information  
800-272-8963 Customer Service  
215-442-8280 (MSDS)  
www.crcindustries.com

00A