

ALL SEASON PERFORMANCE • ALL SEASON PROTECTION

# AVIEX

## PREMIUM ANTI-GEL WITH LUBRICITY

- **LOWERS POUR POINT BY AS MUCH AS 35°F**
- **MAINTAINS AND LUBRICATES INJECTORS**
- **RELIEVES GELLED FUEL**
- **MEETS CUMMINS L-10 TEST FOR INJECTOR CLEANLINESS**

Net Contents: 32 fl.oz. (1Quart) 0.946 L

**DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED.**  
VAPOR HARMFUL. Read warnings on back panel.



Winter can put a real freeze on your fuel system, hindering engine performance and putting your engine at risk. That's why there's **AVIEX® Premium Anti-Gel with Lubricity**. One of the most powerful anti-gels you can use to lower your fuel's pour point and cold filter plugging point (CFPP). Premium Anti-Gel contains no alcohol. Innovative chemical technologies are used to provide you with one of the most effective cold flow improvers on the market today. Diesel fuel quality varies greatly. This product is formulated to impact the largest range of diesel fuel types.

**TREATMENT:** Read entire label before using this product. For best results, add prior to fill-up.

**For preventative maintenance:** This container is sufficient to treat up to 500 gallons of diesel fuel, depending on fuel and temperature.

**To lower pour point:** The following ratios are recommended: One quart treats 125 gallons of fuel to lower pour point by as much as 35°F and CFPP by 30°F (for maximum protection). One quart treats 250 gallons of fuel to lower pour point by as much as 25°F and CFPP by 13°F. One quart treats 500 gallons of fuel to lower pour point by as much as 10°F and CFPP by 5°F.

**To reliquefy gelled fuel:** 1. Remove diesel fuel filter. 2. Fill removed or new filter with **AVIEX® Premium Anti-Gel with Lubricity**. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until full power is restored to engine.

**WARNING:** Contains Petroleum Distillate 64742-94-5 and 64742-95-6, Xylene, 1330-20-7, Ethylbenzene 100-11-4. Overexposure to vapor may cause eye and skin irritation, headaches, nausea, dizziness, irregular heartbeats and irritation to respiratory tract. Product is flammable and should be kept from all flames and other ignition sources. High concentrations have caused liver and kidney effects in laboratory animals. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Use only in a well

ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes.

**FIRST AID:** In case of eye contact, flush with water for 15 minutes. For skin contact, wash with soap and water. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.

#### KEEP AWAY FROM CHILDREN

For additional information, consult the Material Safety Data Sheet for this product.

All used and unused product should be disposed of in accordance with local, state and federal regulations.

**Part No. 405532**  
**Old Part No. 5532**

©2001 CRC Industries, Inc.  
Warminster, PA 18974  
800-521-3168 Technical Information  
800-272-8363 Customer Service  
215-442-6260 (MSDS)  
[www.crcindustries.com](http://www.crcindustries.com)

Made in U.S.A.  
01A  
CRC®913

**CRC**

