

AVIEX®

PREMIUM ANTI-GEL WITH LUBRICITY

Winter can put a real freeze on your fuel system, hindering engine performance and putting your engine at risk. That's why there's AVIEX® Premium Anti-Gel with Lubricity. One of the most powerful anti-gels you can use to lower your fuel's pour point and cold filter plugging point (CFPP). Premium Anti-Gel contains no alcohol. Innovative chemical technologies are used to provide you with one of the most effective cold flow improvers on the market today. Diesel fuel quality varies greatly. This product is formulated to impact the largest range of diesel fuel types.

TREATMENT: Read entire label before using this product. For best results, add prior to fill-up.

For preventive maintenance: This container is sufficient to treat up to 110,000 gallons of diesel fuel, depending on fuel and temperature.

To lower pour point: The following ratios are recommended:

One gallon treats 500 gallons of fuel to lower pour point by as much as 35°F and CFPP by 30°F (for maximum protection). One gallon treats 1000 gallons of fuel to lower pour point by as much as 25°F and CFPP by 13°F. One gallon treats 2000 gallons of fuel to lower pour point by as much as 10°F and CFPP by 5°F.

To reliquify gelled fuel:

Remove diesel fuel filter. 2. Fill removed or new filter with AVIEX® Premium Anti-Gel with Lubricity. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until full power is restored to engine.

AVIEX®

**PREMIUM
ANTI-GEL
WITH
LUBRICITY**

- **LOWERS POUR POINT BY AS MUCH AS 35°F**
- **MAINTAINS AND LUBRICATES INJECTORS**
- **RELIQUEFIES GELLED FUEL**
- **MEETS CUMMINS L-10 TEST FOR INJECTOR CLEANLINESS**

Net Weight: 405 lbs. (183.7 Kg)

Part No. 405555

Old Part No 5555

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL.
Read warnings on side panel.

Storage of this container outside will cause this label to become illegible.

AVIEX

WARNING: Contains Petroleum Distillate 64742-94-5 and 64742-95-6, Xylene 1330-20-7, Ethylbenzene 100-41-4. Overexposure to vapor may cause eye and skin irritation, headaches, nausea, dizziness, irregular heartbeats and irritation to respiratory tract. Product is flammable and should be kept from all flames and other ignition sources. High concentrations have caused liver and kidney effects in laboratory animals. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes.

FIRST AID: In case of eye contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.

KEEP AWAY FROM CHILDREN

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Do not cut or weld containers due to explosive hazard. FOR SPILLS, use proper protective equipment. Take precautions as necessary to prevent contamination of surface or ground waters. For small spills, use absorbent and sweep into closed containers for disposal. For large spills evacuate the area, dike and transfer into containers for disposal.

DISPOSAL: Unused contents and containers must be disposed of in accordance with all federal, state and local regulations. EMPTY containers may be offered to a qualified recycler. Unused contents may be offered to a licensed recycler. DO NOT DUMP INTO SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER.

For additional information, consult the Material Safety Data Sheet for this product.



©2001 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 Technical Information
800-272-8963 Customer Service
215-442-6260 (MSDS)
www.crcindustries.com

CRC4913
Made in U.S.A.
01A