



Powerzo™ 9543 (00756)



Part No. 60015NZ

NET WEIGHT 400 lbs. (181.4 Kg)

Powerzo™ 9543

DANGER: Causes severe skin irritation. Harmful if inhaled. Causes eye and respiratory tract irritation. Combustible liquid. Contains components which may cause cancer. May cause chronic health effects. Read warnings carefully.

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air-supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Vapors of this product may develop a flammable atmosphere. Keep away from flames, sparks, or other ignition sources. Do not cut or weld containers due to explosion hazard. FOR SPILLS, use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal. **DISPOSAL:** Used & unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. **EMPTY** containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. Do not dump into sewers, floor drains, on the ground, or into any body of water.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, **DO NOT** induce vomiting. Immediately call a poison center or doctor. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately. **CAUTION:** Empty containers retain residue (liquid and/or vapor) and can be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH.** Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner. Use with adequate ventilation. Open doors and windows or use other means to ensure fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. For additional information, consult the Safety Data Sheet for this product.

Contains: Hydrocarbon solvent (64741-86-2), Polyether amine (Proprietary), Petroleum naphtha (64742-94-5), Naphthalene (91-20-3).

©2013 CRC Industries, Inc.
Warminster, PA 18974
13A CRC#756 Made in U.S.A.
FOR EMERGENCIES CALL
CHEMTREC
1-800-424-9300

DATE CODE:
Batch No.:



HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	2*	REACTIVITY	0
FLAMMABILITY	2	PERSONAL PROTECTION	B

KEEP OUT OF REACH OF CHILDREN

HAZARD: MINIMAL=0 SEVERE=4