



Copper Anti-Seize

for New Zealand



Part No. 64095NZ

NET CONTENTS: 400 lbs (181.6 Kg)

Read warnings carefully.

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Vapors of this product may develop a combustible atmosphere. Keep away from flames, sparks or other ignition sources.

FOR SPILLS, use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal.

DISPOSAL: Used and unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. Unused contents may be offered to a licensed reclaimer. Do not dump into sewers, on the ground, or into any body of water.

CAUTION: Empty containers retain residue and/or vapors and can be dangerous.
DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and returned to a drum reconditioner.

FIRST AID: Eye Contact: Flush with clear water for at least 15 minutes. If irritation persists, seek medical attention. Skin Contact: Remove contaminated clothing. Wipe excess material from skin. Wash exposed area with water. Skin Injections: High pressure skin injections are serious emergencies. Get medical attention. Inhalation: Remove from area of exposure.

For additional information, consult the Safety Data Sheet for this product.

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	0	REACTIVITY	0
FLAMMABILITY	1	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

- Protects from -65° F (-54°C) to 1800° F (982°C)
- Prevents seizing and galling of threaded surfaces
- Prevents rust and corrosion
- Conforms to Mil-PRF-907E

Warning: Limestone 1317-65-3, Mica 12001-26-2 and Copper 7440-50-8.

©2013 CRC Industries, Inc.
 Warminster, PA 18974
 800-521-3168 (Technical information)
 800-272-8963 (Customer Service)
 215-442-6260 (SDS)
 www.crcindustries.com
 13A Made in U.S.A.
 FOR EMERGENCIES CALL CHEMTREC
 1-800-424-9300

KEEP AWAY FROM CHILDREN