



DO THE JOB RIGHT.

WELDER'S ANTI-SPATTER



- Prevents Welding Spatter Build-Up
- Eliminates Grinding of Spatter
- Water-Based Technology, Leaves No Residue
- Easy Cleanup and Paint-Ready

WARNING!
 CONTENTS UNDER PRESSURE.
 READ WARNINGS ON BACK PANEL.

Net wt. 14oz. / 397 grams

12938 Z



EASTWOOD'S PAINTABLE WELDER'S ANTI-SPATTER SPRAY is an advanced technology water-based protectant that provides a quick and efficient coating to prevent welding spatter from adhering to surrounding metal surfaces. Welder's Anti-Spatter Spray saves time and makes clean-up easy by eliminating the need to chisel, grind or wire brush spatter after welding. The water-based film is easily removed by wiping with a cloth or rag, leaving a surface ready for paint or protective coatings.

DIRECTIONS – READ ENTIRE LABEL BEFORE USING THIS PRODUCT

For personal safety, do not apply while equipment is energized.

1. Shake well and hold can 8" to 12" from surface.
2. Spray a light, even film on area to be welded. Performs best when used on a clean surface.
3. Spray on tips, nozzles and other surfaces to help prevent weld spatter buildup.
4. After welding, wipe or clean area before applying another treatment.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

CONTAINS: Water 7732-18-5, Mineral Oil 8042-47-5, Dimethyl Ether 115-10-6, and Mixed glycerides.

WARNING: Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase the ventilation or leave the area. Avoid continuous breathing of vapors and spray mist. Avoid contact with skin and eyes. Overexposure to vapors or spray mist may cause irritation to eyes, nose or throat. Deliberate misuse by concentrating and inhaling the contents may be harmful or fatal.

FIRST AID: In case of eye contact, flush with water for 15 minutes. If swallowed dilute with several glasses of water. If too much is breathed remove to fresh air. For severe overexposure call a physician immediately.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. For additional information, consult the MSDS for this product.

KEEP OUT OF REACH OF CHILDREN

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec Toll Free Day or Night:
 1-800-424-9300 International Call Collect: (202) 483-7616)

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464
 USA: 1-800-345-1178 Canada: 1-800-820-9042
 International: (610) 323-2200 www.eastwood.com
 © Copyright 2011 Easthill Group, Inc. Made in USA