

Easy and Effective

Protects against wear and corrosion. Lubricates moving parts for smooth, squeak-free operation. Adheres to metal surfaces for long-lasting performance. Quick, convenient spray gets to hard-to-reach places.

APPLICATIONS:

Hinges • Industrial Chains • Latches • Slides
Winches • Overhead Door Tracks • Thrust Bearings
Gears • Cables • Nuts/Bolts • Locks
Guide Rails • Springs • Bushings • Ball Joints
Pivot Points and all external moving parts

DIRECTIONS:

1. Disconnect power source to electrical equipment before spraying.
2. Shake well
3. Clean area to be lubricated
4. Spray in light, even coats
5. Use extension tube for hard-to-reach places

SPRAY GREASE



SPRAY GREASE

WHITE LITHIUM

LUBRICATES AND PROTECTS

No-Hassle Application

DANGER:
EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
CONTENTS UNDER PRESSURE.
Read carefully precautions on back panel.

WARNING: Contains Isohexane 64742-49-0/107-83-5, Petroleum Distillates 64742-52-5, Hydrocarbon Propellant 68476-86-8, and n-Hexane 110-54-3. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is extremely flammable and should be kept from all flames and other ignition sources. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause eye and skin irritation, irritation to upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness or confusion. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area. If ventilation is not adequate, respiratory protection should be used. Product may pose an aspiration hazard if swallowed.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call physician immediately. For additional information, consult SDS for this product. KEEP OUT OF THE REACH OF CHILDREN.

Dispose of used and unused product in accordance with local, state and federal regulations. For Safety Data Sheet visit www.amsoil.com.

AMSOIL INC., Superior, WI 54880 U.S.A. 440140C

Made in U.S.A.



PRODUCT CODE: GSP-SC

0113

NET WEIGHT 10 OZ (284 g)