

## Easy and Effective

Protects against wear and corrosion. Lubricates moving parts for smooth, squeak-free operation. Adheres to metal surfaces for long-lasting performance. Quick, convenient spray gets to hard-to-reach places.

### APPLICATIONS:

Hinges • Industrial Chains • Latches • Slides  
Winches • Overhead Door Tracks • Thrust Bearings  
Gears • Cables • Nuts/Bolts • Locks  
Guide Rails • Springs • Bushings • Ball Joints  
Pivot Points and all external moving parts

### DIRECTIONS:

1. Disconnect power source to electrical equipment before spraying.
2. Shake well
3. Clean area to be lubricated
4. Spray in light, even coats
5. Use extension tube for hard-to-reach places

**SPRAY GREASE**



**SPRAY  
GREASE**

**WHITE  
LITHIUM**

**LUBRICATES  
AND  
PROTECTS**

**No-Hassle Application**

**DANGER:**  
EXTREMELY FLAMMABLE. HARMFUL OR  
FATAL IF SWALLOWED. CAUSES SKIN  
IRRITATION. CONTENTS UNDER PRESSURE.  
Read carefully precautions on back panel.

**WARNING:** Contains hexane isomers 64742-49-0/107-83-5, petroleum distillates 64742-52-5, hydrocarbon propellant 68476-86-8, and n-hexane 110-54-3. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is extremely flammable and should be kept from flames and other ignition sources. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause eye and skin irritation, irritation to upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness or confusion. This product contains chemicals known to the State of California to cause cancer. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area.

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, DO NOT induce vomiting. Call a physician immediately. For additional information, consult the SDS for this product. KEEP OUT OF THE REACH OF CHILDREN.

All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, on the ground, or into any body of water. For Safety Data Sheet visit [www.amsoil.com](http://www.amsoil.com).

AMSOIL INC., Superior, WI 54880 USA

Made in USA



PRODUCT CODE: GSP-SC

101

NET WEIGHT 10 OZ (284 g)