

DANGER Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.



PRECAUTIONARY STATEMENTS Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container. Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing gas, mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

FIRST AID If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.. For more information refer to SDS, or call Jet-Lube® at 713-670-5700.

Contains Hydrotreated light distillates (64742-47-8), Solvent-refined heavy paraffinic distillates (64741-88-4), 4,4-Methylene bis(dibutylthiocarbamate) (10254-57-6), Carbon dioxide (124-38-9), Sodium petroleum sulfonate (68608-26-4), 2,5-Bis(n-octylthio)-1,3,4-thiadiazole (13539-13-4) and Dioctyl disulfide (822-27-5). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

ELECTRICAL SHOCK HAZARD This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

1. Shake well before using.
2. Do not apply to energized equipment.
3. Hold can in vertical position, 12 to 18 inches from surface to be treated.
4. Apply light, even coat over entire surface.

WRL™ WIRE ROPE / CHAIN LUBRICANT

WRL™ is a clear, amber liquid lubricant formulated to extend the life of wire rope and chain by displacing moisture and preventing the formation of rust and corrosion. WRL first penetrates to the rope core, or between the chain pin and roller bushing, to minimize internal friction and then thickens to provide a durable flexible lubricant film. This nondrying, nontacky film will not flake, peel or dry out and is resistant to water washoff and hostile salt environments.

LIMITED WARRANTY: SEE PRODUCT BULLETIN

JET-LUBE, INC.

4849 HOMESTEAD RD., SUITE 232, HOUSTON, TX 77028 • 713-670-5700 • www.jetlube.com
EMERGENCY CHEMTREC: +1-703-527-3887 (International) • 1-800-424-9300 (North America)



Product Code 34041



1107
MADE IN USA



JET-LUBE®

WRL™

**WIRE ROPE AND
CHAIN LUBRICANT**

**LUBRICATES AND PROTECTS
WIRE ROPE, CHAINS, CABLES**

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CAUSES SKIN IRRITATION. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN. Carefully read cautions on back panel.

12 OZ. NET WT. (340 GRAMS)