

Lubricant and Protector

Lubricates moving parts to silence squeaks without gumming up mechanisms. Penetrates deep to free rusty parts. Displaces moisture and helps prevent corrosion. Excellent for protecting firearms and drying electrical systems.

DIRECTIONS: Shake well before use. Spray on area to be treated. For best results, do not wipe off; carrier will evaporate, leaving MP protection in place. **Disconnect power source to electrical equipment before spraying.**



Information

METAL PROTECTOR



MP

METAL PROTECTOR

DANGER: Contains petroleum distillates 64742-47-8, 8052-41-3, & 64742-54-7 and carbon dioxide 124-38-9. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight. Contents are extremely flammable. Keep away from heat, sparks, open flame or other sources of ignition. Do not smoke. Vapors will accumulate readily and may ignite explosively. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause moderate to severe eye and skin irritation, irritation to upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness or confusion. Chronic overexposure may lead to nervous system damage. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Product may pose an aspiration hazard if swallowed. This product may contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area. **FIRST AID:** In case of eye or skin contact, flush with water for at least 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately.

For safety data sheet visit www.amsoil.com. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do NOT dump in sewers, floor drains, on the ground or into any body of water. KEEP OUT OF REACH OF CHILDREN.

AMSOIL INC., Superior, WI 54880 U.S.A.

DOT 2Q M5702 Made in U.S.A.

93010/874A/Rev 13A

PRODUCT CODE: AMP-SC



1213

**Lubricates • Frees Rusty Parts
Protects Against Corrosion
Displaces Moisture**

DANGER:
EXTREMELY FLAMMABLE. VAPORS MAY CAUSE
FLASH FIRES. HARMFUL OR FATAL IF
SWALLOWED. VAPOR HARMFUL. EYE AND SKIN
IRRITANT. CONTENTS UNDER PRESSURE.
Read carefully precautions on back panel.

NET WEIGHT 8.75 OZ (248 g)