




Read entire label before using this product.

ON & OFF HULL & BOTTOM CLEANER

■ REMOVES WATER STAINS INSTANTLY ■ WILL NOT HARM GEL COAT



Part No. MK20550

NET WEIGHT 531 lbs. (241 kg)



DANGER

May be corrosive to metals. Harmful if swallowed. May cause respiratory irritation.

PRECAUTIONARY STATEMENTS

Do not breathe mist or vapor. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container. Do not store container below 32 °F/0 °C. Dispose of contents/container in accordance with local/regional/national regulations. Absorb spillage to prevent material damage.

May cause severe skin burns and eye damage.

FIRST AID

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.

Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

DIRECTIONS: Read entire label before using this product.

Test on a small area prior to use on painted surfaces. Protect boat trailers with a plastic (polyethylene) cover when using ON & OFF. Pour contents into a bucket or other plastic container. Apply full strength with a natural bristle paint brush, then hose off or rinse with water. TO REMOVE RUST STAINS: Apply directly to stain with a natural bristle brush. Wait approximately 60 seconds, then rinse off. If rust is heavily embedded, reapply.

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM		
HEALTH	3	1
FLAMMABILITY	0	D

HAZARD: MINIMAL=0 SEVERE=4

Do not apply while equipment is energized.

- Works instantly to remove the toughest waterline stains, algae stains, rust and gas exhaust stains
- Just brush on & rinse off
- Use on fiberglass only

Contains Water (7732-18-5), Hydrochloric Acid (7647-01-0), Phosphoric Acid (7664-38-2), C12-15 Ethoxylated alcohols (68131-39-5) and Oxalic Acid (144-62-7).

©2015 CRC Industries, Inc.
885 Louis Dr.
Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-8963 (Customer Care)
215-442-6260 (SDS)
www.crcindustries.com
15A Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300

Batch No:
Date Code:

