




# Red Urethane RTL

Part No. R0513



R0513

NET WEIGHT 352 lbs. (160Kg)

**DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. Read warnings carefully.**

**HANDLING AND SPILL PRECAUTIONS:** Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air-supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Vapors of this product may develop a flammable atmosphere. Keep away from flames, sparks, or other ignition sources. Do not cut or weld containers due to explosion hazard. FOR SPILLS, use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal. DISPOSAL: Used & unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. EMPTY containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. Do not dump into sewers, on the ground, or into any body of water.

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately.  
**CAUTION:** Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.

Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience symptoms listed on this label, increase ventilation or leave the area. For additional information, consult the Safety Data Sheet for this product.

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

|              |   |                     |   |
|--------------|---|---------------------|---|
| HEALTH       | 2 | REACTIVITY          | 0 |
| FLAMMABILITY | 3 | PERSONAL PROTECTION | B |

HAZARD: MINIMAL=0 SEVERE=4

**KEEP OUT OF REACH OF CHILDREN**

Red Urethane RTL

Contains: Acetone 67-64-1, Hexane isomers 64742-49-0, Xylene 1330-20-7, Red pigment 1332-37-2, Ethylbenzene 100-41-4, and n-hexane 110-54-3.

DATE CODE:

BATCH No:

©2012 CRC Industries, Inc.  
Warminster, PA 18974  
800-521-3168 (Technical Information)  
800-272-4620 (Customer Service)  
215-442-6260 (SDS)  
www.crcindustries.com  
12A CRC#00507B Made in U.S.A.  
FOR EMERGENCIES CALL  
CHEMTREC  
1-800-424-9300