



GL--5 HD GEAR OIL 85W140

NET 16 GALS

GL - 5 HD GEAR OIL 85W140

NET 16 GALS



MEETS THE SEVERE LUBRICATION REQUIREMENTS OF TRUCK & CAR AXLES EQUIPPED WITH CONVENTIONAL AND LIMITED -SLIP DIFFERENTIALS. RECOMMENDED FOR APPLICATIONS CALLING FOR Mil - L2105E FOR HYPOID GEAR SETS AND AGMA - 7EP INDUSTRIAL TYPE LUBRICANTS. FORMULATED FOR DIFFERENTIALS OPERATING UNDER HIGH SPEED, LOW SHOCK; HIGH SPEED, LOW TORQUE; AND LOW SPEED, HIGH TORQUE CONDITIONS. FOR COMPLETE FILL OR TOPPING OFF OF MANUAL TRANSMISSION, HYPOID TYPE DIFFERENTIALS, LIMITED - SLIP/TWIN GRIP/TRAK - LOK/SURE - GRIP DIFFERENTIALS WHERE 85W140 GRADE IS RECOMMENDED.

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	1	REACTIVITY	0
FLAMMABILITY	1	PERSONAL PROTECTION	X

HAZARD: MINIMAL=0 SEVERE=4

IMPORTANT: DO NOT MIX GREASES OF DIFFERENT BASE TYPE. USE A SOLVENT TO REMOVE AND CLEAN OUT ALL TRACES OF INCOMPATIBLE GREASE BEFORE REPACKING. REPACK ACCORDING TO MANUFACTURERS INSTRUCTIONS.

IMPORTANTE: NO MEZCLE GRASAS DE BASE DIFERENTE.

First Aid: Eye Contact: Flush with clear water for at least 15 minutes.
If irritation persists, seek medical attention.
Skin Contact: Remove contaminated clothing. Wipe excess material from skin. Wash exposed area with water.
Skin Injections: High pressure skin injections are serious emergencies. Get immediate medical attention.
Inhalation: Remove from area of exposure.

CAUTION

Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.



WARNING
Child can fall into bucket and drown. Keep children away from bucket containing any amount of any liquid.

PRODUCT CODE
SL2437

BATCH NUMBER

STA-LUBE®
©1998 CRC Industries, Inc.
Warminster, PA 18974
TECHNICAL INFORMATION: 800-521-3168
CUSTOMER SERVICE: 800-272-8963
Made in USA