



HONING & CUTTING OIL

NET 5 GALS

HONING & CUTTING OIL

EXTREME PRESSURE, ANTI WELD,
LUBRICITY, AND WETTING AGENTS
ALLOW INCREASED SPEED AND FEED
ANTI CORROSION ADDITIVES EXTEND
TOOL LIFE AND IMPROVE MACHINED
SURFACE.

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	1	REACTIVITY	1
FLAMMABILITY	0	PERSONAL PROTECTION	X

HAZARD: MINIMAL=0 SEVERE=4

IMPORTANT: DO NOT MIX GREASES OF DIFFERENT BASE TYPE. USE A SOLVENT TO REMOVE AND CLEAN OUT ALL TRACES OF INCOMPATIBLE GREASE BEFORE REPACKING. REPACK ACCORDING TO MANUFACTURERS INSTRUCTIONS.

IMPORTANT: NO MEZCLE GRASAS DE BASE DIFERENTE.


First Aid: Eye Contact: Flush with clear water for at least 15 minutes.
If irritation persists, seek medical attention.
Skin Contact: Remove contaminated clothing. Wipe excess material from skin. Wash exposed area with water.
Skin Injections: High pressure skin injections are serious emergencies.
Get immediate medical attention.
Inhalation: Remove from area of exposure.

Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION. IT MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.

CAUTION

WARNING

Child can fall into bucket and drown. Keep children away from bucket containing any amount of any liquid.



PRODUCT CODE

SL 2525

BATCH NUMBER



HONING & CUTTING OIL

NET 5 GALS

STA-LUBE®
©1998 CRC Industries, Inc.
Warminster, PA 18974
TECHNICAL INFORMATION: 800-521-3168
CUSTOMER SERVICE: 800-272-8963
Made in USA