



# NEW GENERATION WHEEL BEARING GREASE

NET 120 LBS.

NEW GENERATION  
WHEEL BEARING GREASE

PREMIUM LITHIUM COMPLEX NLGI GC-LB CERTIFIED GREASE FOR USE ON DRUM AND DISC BRAKE WHEEL BEARINGS, CHASSIS, SUSPENSIONS AND UNIVERSAL JOINTS. PROVIDES EXCELLENT PERFORMANCE UNDER EXTREME PRESSURE AND ANTI-WEAR APPLICATIONS. TYPICAL DROP POINT: 500 F.

ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE WITH LOCAL, STATE, AND FEDERAL REGULATION.

CONTAINS: LUBE OIL 64742-52-5, NONANEDIOIC ACID DILLITHIUM SALT 38900-29-7.

**KEEP OUT OF REACH OF CHILDREN**

STA - LUBE IS A WHOLLY - OWNED SUBSIDIARY OF CRC INDUSTRIES, INC.  
TECHNICAL INFORMATION 800-521-3168  
CUSTOMER SERVICE 800-272-8963

[www.crcindustries.com](http://www.crcindustries.com)  
REVISION # 03A

**PRODUCT CODE**  
SL3117  
**BATCH NUMBER**  
3107


### HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

1	REACTIVITY	1
0	PERSONAL PROTECTION	X

**HAZARD: MINIMAL=0 SEVERE=4**

**IMPORTANT: DO NOT MIX GREASES OF DIFFERENT BASE TYPE. USE A SOLVENT TO REMOVE AND CLEAN OUT ALL TRACES OF INCOMPATIBLE GREASE BEFORE REPACKING. REPACK ACCORDING TO MANUFACTURERS INSTRUCTIONS.**

**IMPORTANTE: NO MEZCLAS GRASAS DE BASE DIFERENTE.**



**First Aid: Eye Contact:** Flush with clear water for at least 15 minutes. If irritation persists, seek medical attention.  
**Skin Contact:** Remove contaminated clothing. Wipe excess material from skin. Wash exposed area with water.  
**Skin Injections:** High pressure skin injections are serious emergencies. Get immediate medical attention.  
**Inhalation:** Remove from area of exposure.



**WARNING**  
Child can fall into bucket and drown. Keep children away from bucket containing any amount of any liquid.

**CAUTION**  
Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.

NEW GENERATION WHEEL BEARING GREASE

NET 120 LBS.



STA-LUBE®  
©1998 CRC Industries, Inc.  
Warminster, PA 18974  
TECHNICAL INFORMATION: 800-521-3168  
CUSTOMER SERVICE: 800-272-8963  
Made in USA 98A