Sta-Lube SINCE 1933

WATER-RESISTANT

MARINE GREASE

4WD • BOAT TRAILER • MARINE EQUIPMENT

GRASA RESISTENTE AL AGUA PARA EMBARCACIONES

Part No. SL3121

14 OZ (397G)

WARNING: CAUSES EYE AND SKIN IRRITATION. Read warnings on back panel.

CRC

WATER-RESISTANT

MARINE GREASE

4WD • BOAT TRAILER • MARINE EQUIPMENT

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

- A distinctive tacky grease which resists washout under most severe water conditions
- Superior rust and corrosion protection and high melting point – meets ASTM No. D1743
- Minimizes expansion or pressure build-up in fully packed trailer wheel hubs
- For use on all types of boat trailer wheel bearings, water pumps, steering and cable quadrants, 4WD hubs, sleeve and anti-friction bearings, slides and deck equipment, and dockside machinery
- Para usar en todo tipo de cojinetes para ruedas de remolques para embarcaciones, bombas de agua, cuadrantes de dirección y de cables, ejes de 4WD, cojinetes tipo manga y antifricción, patines y equipamiento de cubierta, y maquinaria del muelle

Sta-Lube® is a wholly-owned subsidiary of CRC Industries, Inc.
©2014 CRC Industries, Warminster, PA 18974
www.crcindustries.com Made in USA 14A

SDS: 215-442-6260
Technical Service: 800-521-3168
Customer Service: 800-272-8963

WARNING: Contains highly refined petroleum distillates 64742-52-5, 64742-65-0 & 64742-53-6, aluminium hydroxide benzoate stearate 54326-11-3 and calcium dinonyl naphthalenesulfonate 57855-77-3. Causes eye and skin irritation. Wash thoroughly after handling. This product contains chemicals known to the State of California to cause cancer. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. In case of skin contact, wash with soap and water. If swallowed, DO NOT induce vomiting. For additional information, consult SDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water. **KEEP AWAY FROM CHILDREN**

0 72213 31210 2

Product Part No. SL3121

TYPICAL SPECIFICATIONS
Base Type: Aluminum Complex
Color: Blue
N.L.G.I. No: Grade 2
Drop Point: 500°F Min.
Water Resistance: Excellent

IMPORTANT: Do not mix greases of different base type. Use a solvent to remove and clean out all traces of incompatible grease before repacking. Repack according to manufacturer's instructions.