



DISC BRAKE HI - TEMP GREASE

NET 120 LBS

DISC BRAKE HI - TEMP GREASE

ALUMINUM COMPLEX, NLGI #2 GRADE GREASE PROVIDES EXTENDED WEAR UNDER HEAVY LOAD AND HIGH SPEED CONDITIONS. MAINTAINS 40 lb. TIMKEN OK LOAD. TYPICAL DROP POINT 470 DEGREES FAHRENHEIT.

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	1	REACTIVITY	1
FLAMMABILITY	0	PERSONAL PROTECTION	X

HAZARD: MINIMAL=0 SEVERE=4

IMPORTANT: DO NOT MIX GREASES OF DIFFERENT BASE TYPE. USE A SOLVENT TO REMOVE AND CLEAN OUT ALL TRACES OF INCOMPATIBLE GREASE BEFORE REPACKING. REPACK ACCORDING TO MANUFACTURERS INSTRUCTIONS.

IMPORTANTE: NO MEZCLE GRASAS DE BASE DIFERENTE.

First Aid: Eye Contact: Flush with clear water for at least 15 minutes.

If irritation persists, seek medical attention.

Skin Contact: Remove contaminated clothing. Wipe excess material from skin. Wash exposed area with water.

Skin Injections: High pressure skin injections are serious emergencies.

Get immediate medical attention.

Inhalation: Remove from area of exposure.

CAUTION

Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION. IT MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.

WARNING

Child can fall into bucket and drown. Keep children away from bucket containing any amount of any liquid.



PRODUCT CODE

SL3167

BATCH NUMBER

5027

DISC BRAKE HI - TEMP GREASE

NET 120 LBS



STA-LUBE®
©1998 CRC Industries, Inc.
Warmster, PA 18974
TECHNICAL INFORMATION: 800-521-3168
CUSTOMER SERVICE: 800-272-8963
Made in USA