



**EXTREME PRESSURE**

**STA-PLEX<sup>TM</sup>**

**PREMIUM RED GREASE**



- Part No. SL3196 •
- Net Wt. 7 lbs. (3.175 kg) •



# EXTREME PRESSURE STA-PLEX™ PREMIUM RED GREASE

## Sta-Plex™ Grasa Superior Roja con Antifriccionante

- High viscosity oils plus a complex lithium soap base give this grease an exceptionally broad temperature range and stability. Polymers and multiple chemical additives provide extreme pressure, anti-wear and anti-oxidant properties.
- Resists poundout and washout under demanding and severe lubrication requirements. 80 lb. Timken OK load prevents wear.
- Resiste fuertes impactos y el agua aún bajo exigencias de lubricación serias. Previene el desgaste con una carga Timken de 80 lb.
- NLGI GC certified grease can provide lubrication continuously at 300°F.
- Authorized by USDA for use in federally inspected meat and poultry plants; H-2 rating.
- Especially suited for the most severe multi-purpose service in construction, manufacturing, farming and fleet industries.
- Especialmente apropiada para las más graves y amplias aplicaciones en las industrias de la construcción, fabricas, agricultura y flotas.

MEETS OR EXCEEDS GM 7841873, 1051344 AND 1052497, CHRYSLER 4318062, MS7097 AND 4318064.

For additional information, consult the material Safety Data Sheet for this product.

Sta-Lube® is a wholly owned subsidiary of CRC Industries, Inc.  
 Technical Service: 1-800-521-3168 • Customer Service: 1-800-272-8963  
 215-442-6260 (MSDS) • [www.crcindustries.com](http://www.crcindustries.com)  
 ©2000 CRC Industries, Inc. • Warminster, PA 18974  
 Made in USA 00A

**WARNING:** Read entire label before using this product. Contains Paraffinic Oil 64742-65-0, Mineral Oil (heavy) 64741-96-4, Zinc Diamyldithiocarbamate 15337-18-5, Lithium Soap 7620-77-1.

**IMPORTANT:** DO NOT MIX GREASES OF DIFFERENT BASE TYPE. USE A SOLVENT TO REMOVE AND CLEAN OUT ALL TRACES OF INCOMPATIBLE GREASE BEFORE REPACKING. REPACK ACCORDING TO MANUFACTURER'S INSTRUCTIONS.

**IMPORTANTE:** NO MEZCLE GRASAS DE DIFERENTE TIPO DE BASE. ANTES DE EMPAQUETAR, USAR UN SOLVENTE PARA REMOVER Y LIMPIAR LOS RASTROS DE GRASA INCOMPATIBLE. EMPAQUETAR DE ACUERDO A LAS INSTRUCCIONES DEL FABRICANTE.

This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm.  
**KEEP OUT OF REACH OF CHILDREN**

### TYPICAL SPECIFICATIONS

- Base Type: 12-Hydroxy Lithium Complex
- Color: Red
- N.L.G.I. No.: Grade 2
- Drop Point: 500° F Min.
- Water Resistance: Excellent
- Timken OK Load: 80 lbs.
- E.P. Performance Load
- Weld Point (4-Ball): 600+ kg.
- Wear Index: 70+ k

